

RoHS COMPLIANT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	MAY. 12'03
B		MODIFY POLES	JAN. 18'07
C		MODIFY P/N	DEC. 08'10

SPECIFICATIONS

- Poles: 2-15
- Voltage rating: 250V AC, DC
- Current rating: 3A, AC, DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 1000M Ω /min
- Temperature range: -25 $^{\circ}$ C~+85 $^{\circ}$ C
- Applicable PC board thickness: .063" (1.6mm)
- Contact resistance: Initial Value/10m Ω max
After environmental testing/20m Ω max

HOUSING

- Poles: 2-15
- Material: Contact: Brass, Tin plated
Base: Nylon 66 UL94V-2
- Q ty: 500,1000pcs/bag

NO.	DIMENSION (mm)	
	A	B
2	2.54	5.60
3	5.08	8.14
4	7.62	10.68
5	10.16	13.22
6	12.70	15.76
7	15.24	18.30
8	17.78	20.84
9	20.32	23.38
10	22.86	25.92
11	25.40	28.46
12	27.94	31.00
13	30.48	33.54
14	33.02	36.08
15	35.56	38.62

TOLERANCE UNLESS
OTHERWISE SPECIFIED

LINEAR	ANGLE
X. $\pm$ 0.50	X $^{\circ}$ $\pm$
.X $\pm$ 0.30	.X $^{\circ}$ $\pm$
.XX $\pm$ 0.20	.XX $^{\circ}$ $\pm$
.XXX $\pm$	.XXX $^{\circ}$ $\pm$

APPD		
CHKD		
DRAW	Z	DEC. 08'2010

PROJECTION



UNITS

MM

SCALE

SIZE

A4



GOLD-TEK ELECTRIC CO., LTD.

TITLE
PITCH: 2.54MM
HOUSING

CPART NO.

PART NO.

8001**

CAD NO. 1056

F:\PDF\HW\HW-0020

SHEET

1 OF 1

圖面編號:GTKSD0007-C(1)