

Crimp Connectors

2.54mm Pitch - Crimp Housings

[Home](#) >> [Connectors & Adaptors](#) >> [Cable Mount](#) >> [Crimp Connectors](#) >> [Modular Connectors](#)

PRODUCTS

[Mechatronics](#)

[Optoelectronics](#)

[Cable Assemblies](#)

[Connectors & Adaptors](#)

[PCB Mount](#)

[Cable Mount](#)

- Coax Connectors
- IDC Connectors
- Crimp Connectors
- Solder Connectors
- Accessories



2.54mm pitch crimp housings available in 2 to 20 way, with or without locking ramps. Current rated at 3 Amps AC per contact.

- [Mates with GTK 2500 series](#)
- Sizes 2 to 20 circuits
- Optional locking ramp
- End-to-end Stackable
- 2.54 mm pitch
- Contact Accept 22-28 wire
- 10,000 contacts per



SERVICES

[UK Manufacturing](#)

[Far East Manufacturing](#)

[Global Support](#)

[Distribution Network](#)

Part Numbers

Specifications

Downloads

Part Number



Pins	With Locking Ramp	Without Locking Ramp
2	2510-02-R	2510-02-NR-R
3	2510-03-R	2510-03-NR-R
4	2510-04-R	2510-04-NR-R
5	2510-05-R	2510-05-NR-R
6	2510-06-R	2510-06-NR-R
7	2510-07-R	2510-07-NR-R
8	2510-08-R	2510-08-NR-R
9	2510-09-R	2510-09-NR-R
10	2510-10-R	2510-10-NR-R
11	2510-11-R	2510-11-NR-R
12	2510-12-R	2510-12-NR-R
13	2510-13-R	2510-13-NR-R
14	2510-14-R	2510-14-NR-R
15	2510-15-R	2510-15-NR-R

Contact Part No: 2510T-R