main

catalog

news

request form

company

local reps

distribution

Tel: (909)596-6298 Fax: (888)HO-CHIEN

# HO CHIEN ELECTRONIC GROUP, INC.

### 2532 Series

## 0.100" Center Shrouded Header

#### Material:

**Contact: Phosphor Bronze** 

Contact Plating: Gold over 0.000100" Nickel Under plating

Insulator: PBT & 30% glass fiber reinforced thermo plastic; rated UL94V-O,

N6: Nylon 6T for high temperature SMT application

Insulator Color: Black or Gray Mating Connector: 2540 Series

#### Electrical:

**Current Rating: 3 Amp Max.** 

Contact Resistance: 30 Milliohms. Max.

Insulation Resistance: 5000 Megohms Min. DC 500V

**Dielectric Strength: 1000V AC** 

Operation Temperature: -55°C to +105°C


Note: Single Row use 2544 pin header w/o Shrouded.






# **Ordering Part Number**

2532 -	[][]		- []	00	
Series Number	Number of Positions	Contact Plating Gold	Housing Color	Housing Material	
2532: Through Hole	6, 8, 10, 12, 14, 16, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48 50, 52, 54, 56, 58, 60, 62, 64	Blank: Gold Flash (All post) F: 10u" Gold (All post) E: 15u" Gold (All post) D: 30u" Gold (All post) Selected Gold: Tin Tail, Au Contact (2mm)	Blank: Black Color G: Gray Color	Blank: Std PBT	Blank: Tray Package
2532M: Surface Mount	6, 8, 10, 12, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50	GT: Gold Flash on Contact area (2mm) FT: 10u" Gold on Contact area (2mm) ET: 15u" Gold on Contact area (2mm) DT: 30u" Gold on Contact area (2mm)		Blank: Nylon 6T	Blank: Tray Package T: Tube CT: CAP Pad w Tube CR: CAP Pad w Tape Reel. Available 10, 14, 16, 20, 26, 34, 40




Dime	ension antitheses	list
NO. Pin	STANDARD(A)	L
6P-8P	2.2	4.00
10P-64P	3.3mm	4.40

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimensions (mm)								
Pos.	A	В	С					
10	20.34	18.10	10.16					
12	22.88	20.58	12.70					
14	25.48	23.18	15.24					
16	27.90	25.72	17.78					
20	33.05	30.80	22.88					
24	38.08	35.88	27.94					
26	40.68	38.42	30.48					



30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.46	56.20	48.26
50	71.10	68.90	60.96
60	83.80	81.60	73.66
64	89.10	86.68	78.74

| Main Menu | On-line catalog | Local Rep | Distribution |
| News | Company | Request Form | E-Mail |

Copyright @ 1995-2012 Ho Chien Electronic Group, Inc. All rights reserved.