



DC COMPONENTS CO., LTD.

DISCRETE SEMICONDUCTORS

2N5551

TECHNICAL SPECIFICATIONS OF NPN EPITAXIAL PLANAR TRANSISTOR

Description


Designed for general purpose amplifier applications.

Pinning

- 1 = Emitter
- 2 = Base
- 3 = Collector

Absolute Maximum Ratings($T_A=25^{\circ}\text{C}$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CB0}	180	V
Collector-Emitter Voltage	V_{CE0}	160	V
Emitter-Base Voltage	V_{EB0}	6	V
Collector Current	I_C	600	mA
Total Power Dissipation	P_D	625	mW
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to +150	$^{\circ}\text{C}$



Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified)




Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Collector-Base Breakdown Voltage	BV_{CB0}	180	-	-	V	$I_C=100\mu\text{A}$, $I_E=0$
Collector-Emitter Breakdown Voltage	BV_{CE0}	160	-	-	V	$I_C=1\text{mA}$, $I_B=0$
Emitter-Base Breakdown Voltage	BV_{EB0}	6	-	-	V	$I_E=10\mu\text{A}$, $I_C=0$
Collector Cutoff Current	I_{CB0}	-	-	50	nA	$V_{CB}=120\text{V}$, $I_E=0$
Emitter Cutoff Current	I_{EB0}	-	-	50	nA	$V_{EB}=4\text{V}$, $I_C=0$
Collector-Emitter Saturation Voltage ⁽¹⁾	$V_{CE(sat)1}$	-	-	0.15	V	$I_C=10\text{mA}$, $I_B=1\text{mA}$
	$V_{CE(sat)2}$	-	-	0.2	V	$I_C=50\text{mA}$, $I_B=5\text{mA}$
Base-Emitter Saturation Voltage ⁽¹⁾	$V_{BE(sat)1}$	-	-	1	V	$I_C=10\text{mA}$, $I_B=1\text{mA}$
	$V_{BE(sat)2}$	-	-	1	V	$I_C=50\text{mA}$, $I_B=5\text{mA}$
DC Current Gain ⁽¹⁾	h_{FE1}	80	-	-	-	$I_C=1\text{mA}$, $V_{CE}=5\text{V}$
	h_{FE2}	80	-	400	-	$I_C=10\text{mA}$, $V_{CE}=5\text{V}$
	h_{FE3}	50	-	-	-	$I_C=50\text{mA}$, $V_{CE}=5\text{V}$
Transition Frequency	f_T	100	-	300	MHz	$I_C=10\text{mA}$, $V_{CE}=10\text{V}$, $f=100\text{MHz}$
Output Capacitance	C_{ob}	-	-	6	pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$, $I_E=0$

(1) Pulse Test: Pulse Width $\leq 380\mu\text{s}$, Duty Cycle $\leq 2\%$

Classification of h_{FE2}

Rank	A	B	C
Range	80~200	100~250	160~400

Electrical Characteristic Curves

Typical Pulsed Current Gain
vs Collector CurrentCollector-Emitter Saturation
Voltage vs Collector CurrentInput and Output Capacitance
vs Reverse VoltageBase-Emitter Saturation
Voltage vs Collector Current