


2SD1792
(TP7L20)

7A NPN

OUTLINE DIMENSIONS



RATINGS

- Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55 ~ +150	
Junction Temperature	Tj		+150	
Collector to Base Voltage	V _{CBO}		200	V
Collector to Emitter Voltage	V _{CEO}		200	V
Emitter to Base Voltage	V _{EBO}		7	V
Collector Current DC	I _C		7	A
Collector Current Peak	I _{CP}		10	A
Base Current DC	I _B		0.5	A
Base Current Peak	I _{BP}		1.0	A
Total Transistor Dissipation	P _T	Tc = 25	30	W
Dielectric Strength	Vdis	Terminals to case AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.3N·m)	0.5	N·m

- Electrical Characteristics (Tc=25)


Item	Symbol	Conditions	Ratings	Unit
Collector Cutoff Current	I _{CBO}	V _{CB} = 200V	Max 0.1	mA
	I _{CEO}	V _{CE} = 200V	Max 0.1	
Emitter Cutoff Current	I _{EBO}	V _{EB} = 7V	Max 5	mA
DC Current Gain	h _{FE}	V _{CE} = 3V, I _C = 3A	Min 1,500	
			Max 30,000	
Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C = 3A	Max 1.5	V
Base to Emitter Saturation Voltage	V _{BE(sat)}	I _B = 5mA	Max 2.0	V
Thermal Resistance	θ jc	Junction to case	Max 4.16	/W
Transition Frequency	f _T	V _{CE} = 10V, I _C = 0.7A	TYP 20	MHz
Turn on Time	ton	I _C = 3A I _{B1} = I _{B2} = 5mA R _L = 10Ω V _{BB2} = 4V	Max 2	μ s
Storage Time	ts		Max 12	
Fall Time	tf		Max 5	

2SD1792

$h_{FE} - I_C$




2SD1792 Saturation Voltage




2SD1792

Switching Time - I_C




2SD1792

Switching Time - T_c




2SD1792 Transient Thermal Impedance




2SD1792

Forward Bias SOA



2SD1792 Collector Current Derating



2SD1792

Reverse Bias SOA

