



Strain Relief Bushings

- Thermoplastic material, flame-retardant according to UL 94V-2.
- Maximum temperature on part not to exceed 75°C (167°F).
- Secure and protect power cords from being damaged by chassis.
- For use at the entry points of electrical and lighting fixtures.
- Assembly tool is available upon request.



Cross Section Shape	Cat. No.	UL Wires Accommodated	Approx. Wire Size (mm)	Mounting Hole		Max. Thickness F mm	Length D mm	Approval	Packing	
				A mm	B mm				Bag	Carton
Flat (Black)	2P-4	SPT-1	3X5,6	9,5	8,7	1,6	10,4	UL E	1,000	20,000
	3P-4	SPT-1	3X5,6	11,0	9,9	1,6	10,4	UL E	1,000	10,000
	3W-1	SPT-1	3x5,6	11,0	9,9	2,5	10,4	UL E	1,000	10,000
	4N-4	SPT-2	$\frac{3,7}{3,8 \times 7,6}$	12,7-13,1	11,8	1,6	10,4	UL E	1,000	10,000
	4K-4	SPT-2	$\frac{3,7}{3,8 \times 7,6}$	12,7-13,1	11,8	2,5	10,4	UL E	1,000	10,000
Round (Black)	5N-4	SVI / SVT	6,4Ø-7,4Ø	12,7-13,1	11,5	1,6	11,0	UL E	1,000	10,000
	5P-4	SVI / SVT	6,4Ø-7,4Ø	12,7-13,1	11,5	2,5	11,0	UL E	1,000	10,000
	6N-4	SJT 3C #18	7,6Ø	15,9	14,0	1,6	14,8	UL E	500	5,000
	6P-4	SJT 3C #18	7,6Ø	15,9	14,0	3,2	14,8	UL E	500	5,000
	6N3-4	SJT 3C #16	8,2Ø-9,2Ø	15,9	14,0	1,6	14,9	UL E	500	5,000
	6P3-4	SJT 3C #16	8,2Ø-9,2Ø	15,9	14,0	3,2	14,8	UL E	500	5,000
	7N-2	SJT 3C #14	$\frac{9,2Ø-10,5Ø}{11,0Ø}$	$\frac{19,0}{19,8}$	16,8	1,6	19,3	UL E	100	2,000
	7P-2	SJT 3C #14	$\frac{9,2Ø-10,5Ø}{11,0Ø}$	$\frac{19,0}{19,8}$	16,8	3,2	19,3	UL E	100	2,000



Maximum chassis thickness part actually has additional clearance.

Assembly Tool No. 1



Assembly Procedure:

