



PRESSURE ADAPTER

Model : PS-403

- * 1 mV per kPa, psi, cm-Hg, in-Hg.
- * Pressure : 0.5 to 500 psi.
- * Vacuum : 0 to 29.99 in-Hg
- * Port Connector : 1/4" NPT or 1/4" PS, included one adapter connector that convert the 1/4" NPT to 1/4" PS.
- * Sensor material : Ceramic.
- * Weight : 285 g.
- * Meter Size : 100 x 50 x 25 mm.
- * Pressure Sensor Size : 70 mm x 30 mm Dia.
- * Cable length : Approx. 1 meter.
- * Applications : Measure pneumatic pressures, measure automobile engine vacuum pressures, pressure for super heat measurements, hydraulic servo controls, refrigeration, air conditioning, food processing



SOFT CARRYING CASE

Model : CA-03, CA-06, CA-05A, CA-52A

- CA-03 : Soft carrying case (190 x 90 x 55 mm)
- CA-04 : Soft carrying case (140 x 77 x 40 mm)
- CA-05A : Soft carrying case with sash (260 x 110 x 55 mm)
- CA-52A : Soft carrying case with sash (200 x 80 x 50 mm)

CA-05A
CA-52A



CA-03 CA-04



ANEMOMETER ADAPTER

Model : AM-402

- * Measurement : m/s, km/h, ft/min, knots.
- * Output : 1 mV per 1 m/s, per 1 km/h, per 100 ft/min, per 1 knots.
- * Size : 100x50x25 mm, Sensor-72 mm Dia.



SOUND ADAPTER

Model : SL-406

- * Frequency and time weighting meet IEC 61672 class 2.
- * A frequency weighting.
- * Range : 3 ranges, 30 to 130 dB.
- * Output : 1 mV per 1 dB.
- * External Calibration adj. VR.



EMF ADAPTER

Model : EMF-824

- * Electromagnetic field radiation adapter.
- * Range : 20 micro Tesla, 200 milli-Gauss.
- * 1 m Gauss (0.1 u Tesla) per 1 DC mV.
- * Size : 100x50x25 mm.-main instrument.



LIGHT ADAPTER

Model : LX-02

- * 3 ranges, 2,000/20,000/50,000 Lux
- * Output : 0.1 mV per 1 Lux (range A).
0.1 mV per 10 Lux (range B).
0.1 mV per 100 Lux (range C).
- * Size (main instrument) : 100x50x25 mm.

CA-06
CA-08



HARD CARRYING CASE

- CA-06 : Hard Carrying case. (280 x 195 x 65 mm)
- CA-08 : Hard Carrying case. (370 x 310 x 115 mm)

HIGH VOLTAGE PROBE

Model : HV-40

- * DC : 0 to 40 KV, AC : 28 KV rms.
- * 1000 M input impedance, 1/1000 att.
- * DCV : $\pm 1\%$ (1 to 20 KV), $\pm 1.5\%$ (>20kV).
- * ACV : $\pm 5\%$ (>1 KV, 50/60Hz).
- * Size : 340 x 30 x 30 mm.

