

Technical Specification:

Cn (μF)	Un (V)	I _{max} (A)	dv/dt (V/μs)	Ls (nH)	U t-t (V)	U t-c (V)	tgδ (20°C,10kHz)	Size (mm)
CBB15(SFPEC)								
0.47	1200VDC	7	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	46×18×34
1	1200VDC	15	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	46×34×36
2	1200VDC	25	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	50×46×50
3	1200VDC	35	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	50×46×50
30	1250VDC	30	200	≤10	1800V, 10S	3000VAC,60S	≤100×10 ⁻⁴	74×46×49
40	1250VDC	40	200	≤10	1800V, 10S	3000VAC,60S	≤100×10 ⁻⁴	75×50×44
CBB16(SFPEC)								
2	500VAC	25	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	63×49
3	500VAC	35	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	63×49
4	500VAC	50	1200	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	63×49
5	500VAC	60	1300	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	63×49
6	500VAC	80	1400	≤10	1800V, 10S	3000VAC,60S	≤10×10 ⁻⁴	76×49
10	1400VDC	18	200	≤10	1800V, 10S	3000VAC,60S	≤30×10 ⁻⁴	50×60
20	1400VDC	35	200	≤10	1800V, 10S	3000VAC,60S	≤50×10 ⁻⁴	50×60
50	350VAC	35	200	≤10	600V, 10S	3000VAC,60S	≤55×10 ⁻⁴	50×60

Note: Other specifications and size outside table are negotiable.