ROTARY CHANGE OVER SWITCHES

PANEL MOUNT



1 – 4 POLE 16 – 160 AMP 5,5 kW - 75kW

ENCLOSED



1 – 4 POLE 16 – 160 AMP 5,5 kW - 75kW WITH OR WITHOUT PILOT LIGHTS UP TO 63A IN PLASTIC ENCLOSURE 125A AND ABOVE IN METAL ENCLOSURE

PRODUCT INTRODUCTION

This range of rotary switches mainly apply to 440v and below, AC 50Hz or 240V and below DC circuits. For breaking and closing, change-over of circuits under infrequently manual operation. The typical applications are:

- Power Supply to Generator Changeover
- Auto/Manual changeover
- Standby/Remote Changeover and other special application circuits.
- Mainly used in Distribution Panels, UPS etc.

This range complies with GB 14048.3, GB 14048.5 and IEC 60947-3, IEC 60947-5-1

The range currently has 8 ratings; 16A, 20A, 25A, 32A, 40A, 63A, 125A and 160A

SPECIFICATIONS

			16A	20A	25A	32A	40A	63A	125A	160A
Rated insulation			660/	660/	660/	660/	660/	660/	660/	660/
Voltage	Ui	V	690	690	690	690	690	690	690	690
Rated Thermal			16	20	25	32	40	63	125	160
Current	lth	А								