

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
△	15-0428	The plating change to Ni and update the drawing frame.	XHY	09/21/15"

NOTES1:

UL Standard

1. Rated Voltage/Current : 600V / 65A
2. Torque Value : M5 , 22Lb.in
3. Wire Range : 14~6AWG

NOTES2:

1. Dimension shall be interpreted per ASME Y14.5-2009
2. Pitch : 16.0mm, Poles : N=2-20P
3. Withstanding Voltage : AC2200V/1Min.
4. Operating temperature: -40°C~+105°C
5. Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm					—	∠
TO	Over	TO	Over	TO	Over	TO	TO	TO
6	6	10	10	30	30	60	100	150
10	10	24	24	60	60	100	150	150

6. RoHS Compliance

ITEM	NAME OF PART	MATERIAL	NOTES
4	SCREWS	STEEL	M5/Ni Plated
3	NUT	STEEL	M5/Ni Plated
2	HOUSING	PA66	UL94V-0
1	SOLDER PIN	COPPER ALLOY	Sn Plated

PART NO.:

APPD:

CHKD:

DRFT:

/

XHY 12/12/13"

THIRD ANGLE PROJECTION

DEGSON®

NAME:

DG88-XXP-1Y-00A(H)

TITLE:

CUSTOMER DRAWING

DRAWING NO.:

DG88-C01

SHEET

1/1

SCALE

1:1

宁波高松电子有限公司

NINGBO DEGSON ELECTRICAL CO., LTD

REV

T1

DO NOT SCALE DRAWING

SCALE

1:1

