

MEAN WELL SWITCHING POWER SUPPLY ISO-9001 CERTIFIED MANUFACTURER

DKE10A SERIES

.2:1 WIDE INPUT RANGE		ACE / LOW COST						
.4:1 INPUT IS AVIALABLE	SHORT CIRCUI		1					
REGULATED DC OUTPUT		OVER CURRENT PROTECTION						
.500VDC I/P ISOLATION	.FREE AIR CONVECTION							
1K-3KVDC ISOLATION IS AVAILABLE .LOW PROFILE / SMALL SIZE	.100% BURN-IN TEST							
.EPOXY ENCAPSULATED	.1 YEAR WARRANTY							
MODEL	DKE10A-05	DKE10A-12	DKE10A-15	DKE10A-24				
DC OUTPUT VOLTAGE	±5V	±12V	±15V	±24V				
OUTPUT VOLTAGE ACCURACY	±2%							
OUTPUT RATED CURRENT	±1000mA	±420mA	±333mA	±210mA				
OUTPUT CURRENT RANGE	100-±1000mA	42-±420mA	33.3-±333mA	21-±210mA				
RIPPLE & NOISE	50mVp-p	60mVp-p	60mVp-p	80mVp-p				
LINE REGULATION	± 0.3%	±0.3%	±0.3%	±0.3%				
LOAD REGULATION	± 2%	± 2%	± 2%	± 2%				
DC OUTPUT POWER	10W	10W	10W	10W				
EFFICIENCY	82% (TYPICAL)							
SWITCHING FREQUENCY	300KHz (TYPICAL)							
INPUT VOLTAGE RANGE	9-18VDC							
INPUT CURRENT	1.1A/12VDC; 23mA @ NO LOAD (TYPICAL)							
SHORT CIRCUIT PROTECTION	CONTINOUS							
OVER CURRENT PROTECTION	160-250% AUTO RECOVERY							
TEMP. COEFFICIENT	±0.02% / °C (0-50°C)							
ISOLATION VOLTAGE	/P-O/P:500VDC MIN.							
ISOLATION RESISTANCE	//P-O/P:500VDC / 100M Ohms MIN.							
TRANSIENT RESPONSE	250u sec. FOR 25% LOAD STEP CHANGE							
WORKING TEMP., HUMIDITY	-15°C~+60°C, 20%-90% RH (NO DERATING); 80% LOAD @ 71°C							
STORAGE TEMP., HUMIDITY	-13 C-160 C, 20%-90% RH (NO DERATING), 80% LOAD @ 71 C							
DIMENSION	2"*1"*0.42"							
WEIGHT	32g							
CASE METERIAL	SIX-SIDED SHIELD METAL CASE							
MECHANISM AND PIN CONFIGURATION	→ 15.3 → 2	· · · ·	.0 +10.6 Pin no.	Output				
	10.1	3° 2.5		-Vin				
	<u>-</u> 01	40		+Vout				
	· · · · · · · · · · · · · · · · · · ·	COM						
	10.2 воттом	VIEW ^S O		-Vout				
NOTE : 1.ALL PARAMETERS ARE SPECIFIED A								
2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR. 3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.								
4.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD. 2000-04-17								



MEAN WELL SWITCHING POWER SUPPLY ISO-9001 CERTIFIED MANUFACTURER

DKE10B SERIES

.2:1 WIDE INPUT RANGE .4:1 INPUT IS AVIALABLE .REGULATED DC OUTPUT .500VDC I/P ISOLATION .1K-3KVDC ISOLATION IS AVAILABLE .LOW PROFILE / SMALL SIZE .EPOXY ENCAPSULATED	.HIGH PERFORMACE / LOW COST .SHORT CIRCUIT PROTECTION .OVER CURRENT PROTECTION .FREE AIR CONVECTION .100% BURN-IN TEST .1 YEAR WARRANTY						
MODEL	DKE10B-05	DKE10B-12	DKE10B-15	DKE10B-24			
DC OUTPUT VOLTAGE	±5V	±12V	±15V	±24V			
OUTPUT VOLTAGE ACCURACY	±2%						
OUTPUT RATED CURRENT	±1000mA	±420mA	±333mA	±210mA			
OUTPUT CURRENT RANGE	100-±1000mA	42-±420mA	33.3-±333mA	21-±210mA			
RIPPLE & NOISE	50mVp-p	60mVp-p	60mVp-p	80mVp-p			
LINE REGULATION	± 0.3%	±0.3%	±0.3%	±0.3%			
LOAD REGULATION	± 2%	± 2%	± 2%	± 2%			
DC OUTPUT POWER	10W	10W	10W	10W			
EFFICIENCY	84% (TYPICAL)						
SWITCHING FREQUENCY	300KHz (TYPICAL)						
INPUT VOLTAGE RANGE	18-36VDC						
INPUT CURRENT	0.55A/24VDC; 13mA @ NO LOAD (TYPICAL)						
SHORT CIRCUIT PROTECTION	CONTINOUS						
OVER CURRENT PROTECTION	160-250% AUTO RECOVERY						
TEMP. COEFFICIENT	±0.02% / °C (0~50°C)						
ISOLATION VOLTAGE	/P-O/P:500VDC MIN.						
ISOLATION RESISTANCE	//P-O/P:500VDC / 100M Ohms MIN.						
TRANSIENT RESPONSE	250u sec. FOR 25% LOAD STEP CHANGE						
WORKING TEMP., HUMIDITY	-15°C~+60°C, 20%~90% RH (NO DERATING); 80% LOAD @ 71°C						
STORAGE TEMP., HUMIDITY	-25°C~+85°C, 10%~95% RH						
DIMENSION	2"*1"*0.42"						
WEIGHT	32g						
CASE METERIAL	SIX-SIDED SHIELD METAL CASE						
MECHANISM AND PIN CONFIGURATION	→ 15.3 → 20 10.1 5.1 0 2 10.2 BOTTOM			No. Output 1 +Vin 2 -Vin 3 +Vout 4 COM 5 -Vout			
NOTE: 1.ALL PARAMETERS ARE SPECIFIED AT RATED INPUT, RATED LOAD, 25° C 70% RH. AMBIENT. 2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12° TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR. 3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD. 4.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD. 2000-04-17							



MEAN WELL SWITCHING POWER SUPPLY ISO-9001 CERTIFIED MANUFACTURER

DKE10C SERIES

.2:1 WIDE INPUT RANGE .4:1 INPUT IS AVIALABLE .REGULATED DC OUTPUT .500VDC I/P ISOLATION .1K-3KVDC ISOLATION IS AVAILABLE .LOW PROFILE / SMALL SIZE .EPOXY ENCAPSULATED	.HIGH PERFORMACE / LOW COST .SHORT CIRCUIT PROTECTION .OVER CURRENT PROTECTION .FREE AIR CONVECTION .100% BURN-IN TEST .1 YEAR WARRANTY						
MODEL	DKE10C-05	DKE10C-12	DKE1	DC-15	DKE10C-24		
DC OUTPUT VOLTAGE	±5V	±12V	±1	5V	±24V		
OUTPUT VOLTAGE ACCURACY	±2%						
OUTPUT RATED CURRENT	±1000mA						
OUTPUT CURRENT RANGE	100-±1000mA	42-±420mA	33.3-±	333mA	21-±210mA		
RIPPLE & NOISE	50mVp-p	60mVp-p	60m'	Vp-p	80mVp-p		
LINE REGULATION	± 0.3%	±0.3%	±0.	3%	±0.3%		
LOAD REGULATION	±2%	±2%	±2	.%	±2%		
DC OUTPUT POWER	10W	10W	10	W	10W		
EFFICIENCY	85% (TYPICAL)						
SWITCHING FREQUENCY	300KHz (TYPICAL)						
INPUT VOLTAGE RANGE	36-72VDC						
INPUT CURRENT	0.28A/48VDC; 12mA @ NO LOAD (TYPICAL)						
SHORT CIRCUIT PROTECTION	CONTINOUS						
OVER CURRENT PROTECTION	160~250% AUTO RECOVERY						
TEMP. COEFFICIENT	±0.02% / °C (0~50°C)						
ISOLATION VOLTAGE	//P-O/P:500VDC MIN.						
ISOLATION RESISTANCE	//P-O/P:500VDC / 100M Ohms MIN.						
TRANSIENT RESPONSE	250u sec. FOR 25% LOAD STEP CHANGE						
WORKING TEMP., HUMIDITY							
STORAGE TEMP., HUMIDITY	-25°C~+85°C, 10%~95% RH						
DIMENSION	2"*1"*0.42"						
WEIGHT	32g						
CASE METERIAL	SIX-SIDED SHIELD METAL CASE						
MECHANISM AND PIN CONFIGURATION	+ 15.3 → 20 10.1 5.1 0 1 0 2 10.2 Воттом	3 ♥ <u>2.5</u> 4 0 <u>10.2</u> 10.2 10	4.0 →10.5 •	Pin no. 1 2 3 4 5	Output +Vin -Vin +Vout COM -Vout		
Image: Note in the image: I							