




C5e MOUNT BOX STP 6u



99

50



25



Performance:

Meets C5e EIA/TIA 568B Standard.

Materials:

- Body : ABS
- Jack : 8P8C 6 micro inches gold plated
- PCB : FR-4 / UL-94V0
- IDC Body : Fireproof ABS UL-94V0
- IDC Pin : Bronze & Tinned

IDC Description : For 22-26 AWG.
For 110 or Krone punch-down Tool

Electrical Specifications:

- Insulation Resistance : 500M ohms (min.)
- Contact Resistance : 20m ohms (max.)
- Current Rating : 1.5 Amps .
- DC Resistance : 0.1 ohms (max.)
- Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

- IDC Punch Down Cycle : Over 250 Cycles (min.)
- Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

DRAW NO:	ITEM NO:	ITEM NO:	ITEM NO:
UNIT: m/m	APPR	CUSTOMER:	EBX-S1XA6
SCALE:	DESIGN	DATE:	
	Ref. NO:	TOLERANCE:	± 1 · X ± 0.2 · XX ± 0.15