


MEC®

CONFORMAL COATED INDUCTOR

ISSUE DRAWING		2000 / 01 / 10		OUR P/N		EC24-1R0K	
 UNIT: MM						A	3 MAX
						B	8 MAX
						C	30 ± 3
						D	0.50± 0.05
						E	
						F	
						G	
						H	
TERMINAL	WIRE SIZE	TURNS				NOTE	
S-----F	0.12MM	10.2 TS					
TEST CONDITION: TEMPERATURE @25°C HUMIDITY @ 65 ± 5%							
TEST INSTRUMENT	HP.4342A Q---METER			1 KHZ			
	TEST FREQ. @25.2MHZ			100-LCR			
TEST TERMINAL	Q	S . R . F	INDUCTANCE (uH)	D . C . R RESISTANCE	RATED . DC CURRENT		
S-----F	MIN	(MHZ) MIN	± 10%	(OHM) MAX	(mA) MAX		
	65	180	1.0	0.12	700		
ELECTRICAL CHARACTERISTICS							
MATERIAL							
S-----F			LY			WIRE	
CODE			LY 9 2.3 x 4			0.12MM	
DATE	MANUFACTURER		SIZE	MATERIAL		UL FILE NO.	
MAGNET WIRE	PACIFIC CO KOK HONG CO		0.12MM	POLYURETHANE ENA MELLED. WIRE(USE TYPE: 2) OR EQUIVALENT		E84081 (S) E94064 (S)	

MOBICON GROUP