

L45516A /B

Auto J & DC P to auto P W/3A fuse W/LED (24AWG/9')
(molding)
A : 2.1 x 5.5mm
B : 2.5 x 5.5mm

**L455290**

Auto plug/lighter jack to jack W/10A fuse (18AWG/3')

**L45517A /B**

Auto J & DC P to auto P W/3A fuse W/LED (24AWG/9')
(molding)
A : 2.1 x 5.5mm
B : 2.5 x 5.5mm

**L455293**

Auto plug to auto twin jacks
W/light ring, battery checker & 10A fuse (18AWG/3')

**L45518**

DC J & DC '+' P to auto P W/3A fuse W/LED (24AWG/15cm)

**L455295**

Auto plug/lighter jack to auto twin jacks
W/light ring, battery checker & 10A fuse (18AWG/3')

**L45524**

30A battery clip to auto P W/5A fuse W/LED (18AWG/1')

**L45530**

Auto plug to auto three jacks (18AWG/34")

**L45525**

30A battery clip to auto P W/5A fuse (18AWG/1')

**L45531**

Auto plug to auto four jacks (18AWG/40cm)

**L45526**

30A battery clip to auto J (18AWG/1')

**L45535**

. Battery tester
Rating : 5V-30V DC
. Voltage LED display :
LED 3 digitals
. Compact & portable
. Large, easy-to-read LED digital
display to show voltage reading
. Auto detective display of battery
voltage for 12V as well as 24V
. The reading for voltage display
& LED indicators :

Voltage Reading	Low. (red)	Med. (amber)	High (green)
5.0 ~ 11.7V	●		
11.8 ~ 12.4V	●	●	
12.5 ~ 15.9V	●	●	●
16.0 ~ 23.5V	●		
23.6 ~ 24.9V	●	●	●
25.0 ~ 30.0V	●	●	

