





Terminal block
02-30 pin



Item	A	B	C	D	E	F	Rated
X9780Qxx	8.25	8.25x(P+2)	8.25x(P+1)	13.7	6.5	14.7	300V15A
X9780Rxx	9.5	9.5x(P+2)	9.5x(P+1)	17.8	8.0	15.0	300V15A

Terminal block (right angle)
02-30 pin


Item	A	B	C	D	E	F	Rated
X9782Qxx	8.25	8.25x(P+2)	8.25x(P+1)	13.7	6.5	14.7	300V15A
X9782Rxx	9.5	9.5x(P+2)	9.5x(P+1)	17.8	8.0	15.0	300V15A

Terminal block
02-28 pin



Item	A	B	C	D	E	F	Rated
X9784Axx	9.5	9.5xP+17.0	9.5x(P+1)	19.5	7.5	11.9	600V10A
X9784Cxx	10.9	10.9xP+19.9	10.9x(P+1)	22.0	9.0	13.2	600V20A
X9784Dxx	14.0	14.0xP+24.0	14.0x(P+1)	34.0	12.0	17.0	600V30A

Terminal block (double deck)
02-26 pin



Item	A	B	C	D	E	F	Rated
X9786Cxx	8.25	(8.25xP)+1.5	8.25x(P-1)	27.0	6.5	20.0	250V15A

Terminal block with cover (double deck)
02-60 pin

ITEM	A	B	C	D	E	F	Rated
X9788Cxx	7.62	7.62x(P-1)+13.28	7.62x(P-1)	19.5	6.5	22.5	300V15A

Solid terminal block
Glass reinforced plastic ensures
heat-resistance, good toughness
3, 4, 6, 12 pin

Item	A	B	C	D	E	F	Rated
X9789A03	9.1	46	36	22	7.5	17.5	600V 15A
X9789A04	9.1	55	45	22	7.5	17.5	600V 15A
X9789A06	9.1	73	63	22	7.5	17.5	600V 15A
X9789A12	9.1	127	117	22	7.5	17.5	600V 15A

Solid terminal block
Glass reinforced plastic ensures
heat-resistance, good toughness
3, 4, 6, 12 pin

Item	A	B	C	D	E	F	Rated
X9789B03	12	55.5	45	30	10	19.5	600V 25A
X9789B04	12	68	57	30	10	19.5	600V 25A
X9789B06	12	92	81	30	10	19.5	600V 25A
X9789B12	12	164	152	30	10	19.5	600V 25A