

according to Regulation (EC) No 1907/2006

# Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 1 of 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Flux-Off

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Uses advised against

Reserved for industrial and professional use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax:++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit Mo Do. 8.00 - 16	.30 Fr. 8.00 - 14.00
	Swiss Toxicological Information Centr	re - Téléphone : +41 44 251 51 51 (in
	Switzerland dial 145)	
	United Kingdom : National Poisons In 8448920111	formation Service - Phone number :
	Österreich : Vergiftungsinformationsz 406 43 43	entrale Vienna - Telefon-Nummer : +43 1
	Schweiz : Tox Info Suisse - Telefon-N	lummer:+41 44 251 51 51
	Italia : Centro Antiveleni, Roma - Nun	nero di telefono : +39 06 305 4343
	España : Instituto Nacional de Toxico	logía - Teléfono : +34 91 562 04 20
1.4. Emergency telephone	Deutschland: ++49(0)7041-96340	

#### number:

**SECTION 2: Hazards identification** 

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause respiratory irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

### Hazard components for labelling

n-butyl acetate Isopropanol aromatic hydrocarbons

# Signal word: Pictograms:





according to Regulation (EC) No 1907/2006

### Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 2 of 8

### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

obuditionaly otationion	
P211	Do not spray on an open flame or other ignition source.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Special labelling of certain mixtures EUH066 Repeated e

Repeated exposure may cause skin dryness or cracking.

### **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification		•	
	Hydrocarbons, C9, aromatics			20-40%
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT S H411	SE 3, Asp. Tox. 1, Aquatic	Chronic 2; H226 H335 H336 H304	
67-63-0	propan-2-ol; isopropyl alcohol; iso	propanol		30-35%
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	E 3; H225 H319 H336		
123-86-4	n-butyl acetate			15-20%
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H	336 EUH066	·	
109-87-5	Dimethoxymethane			5-10%
	203-714-2		01-2119664781-31	
	Flam. Liq. 2, Eye Irrit. 2; H225 H3			
107-98-2	1-Methoxy-2-propanol			5-10 %
	203-539-1		01-2119457435-35	
	Flam. Liq. 3, STOT SE 3; H226 H			
124-38-9	Carbondioxide		5-10%	
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**



according to Regulation (EC) No 1907/2006

### Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 3 of 8

### 4.1. Description of first aid measures

#### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

#### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

If swallowed, immediately drink: Water.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

#### Unsuitable extinguishing media

Water with tenside additive. Water.

### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

### 6.3. Methods and material for containment and cleaning up

Ventilate affected area.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities



### according to Regulation (EC) No 1907/2006

# Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 4 of 8

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

## Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
109-87-5	Dimethoxymethane	1000	3160		TWA (8 h)	WEL
		1250	3950		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

### 8.2. Exposure controls





#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

#### Eye/face protection

Tightly sealed safety glasses.

#### Hand protection

DIN EN 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

### Skin protection

Protective clothing:

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.



according to Regulation (EC) No 1907/2006

## Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 5 of 8

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Aerosol colourless characteristic		
Changes in the physical state Initial boiling point and boiling range:		82,4 °C	
Flash point:		<0 °C	
Lower explosion limits: Upper explosion limits:		1,2 vol. % 12 vol. %	
Ignition temperature:		270 °C	
Vapour pressure: (at 20 °C)		40 hPa	
Density (at 20 °C):		0,84 g/cm <sup>3</sup>	
Solvent content:		95%	

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No data available

## 10.2. Chemical stability

No data available

### 10.3. Possibility of hazardous reactions

No data available

# 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

# 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

No data available

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### Irritation and corrosivity

Irritating to eyes. Following inhalation: Lung irritation. Coughing. shortage of breath. After skin contact: irritant.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.



### according to Regulation (EC) No 1907/2006

### Flux-Off

Revision date: 09.10.2019

Product code: 107

Page 6 of 8

#### Waste disposal number of waste from residues/unused products 160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIS

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### Waste disposal number of contaminated packaging 150104 WASTE PACKAGING: ABSORBENTS

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 625
Limited quantity:	1 L
Transport category: Tunnel restriction code:	2 D
	D
Other applicable information (land trans E0	ροπ)
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Other applicable information (inland wat E0	erways transport)
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2, see SP63
	,

according to Regulation (EC) No 1907/2006

Revision date: 09.10.2019

Product code: 107

Page 7 of 8

Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity:	See SP277	
EmS:	F-D, S-U	
Other applicable information (marine tra E0	ansport)	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN1950	
14.2. UN proper shipping name:	AEROSOLS, flammable	
14.3. Transport hazard class(es):	2.1	
Hazard label:	2.1	
Special Provisions:	A145 A167	
Limited quantity Passenger:	30 kg G	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	75 kg 203	
IATA-max. quantity - Cargo:	150 kg	
Other applicable information (air transp E0 : Y203	ort)	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	yes	¥2
Danger releasing substance:	Solvent Naphta Light	v
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regu	lations/legislation specific for the subst	ance or mixture
EU regulatory information		
2004/42/EC (VOC):	6,45 % (54,18 g/l)	
National regulatory information		
Water contaminating class (D):	2 - clearly water contaminating	
SECTION 16: Other information		

### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.



according to Regulation (EC) No 1907/2006

Flux-Off		
Revision date: 09.10.2019	Product code: 107	Page 8 of 8
H319 Causes serious eye irritation.		
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
EUH066 Repeated exposure may cause skin dryness or cracking.		

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)