

KINGDOM ELECTRONICS CC

Electronic Design and Manufacture Security & Access Control Equipment

PO Box 1940 • HONEYDEW • 2040 Tel: (011) 791 1362/3749 • Fax: (011) 791 6610

E-mail: ke-sa@mweb.co.za Website: www.kesa.co.za

TECHNICAL PRODUCT BULLETIN

Guard Alert Timer

Application

- Keep Security personal awake.
- Ensure guard patrols occur.

Specifications

- 12VDC operation.
- Current drain 5,7mA standby.
- Positive reset input.
- 30 second Beeper alert after time expires.
- Adjustable time setting 15min, 30min, 60min, 90min.
- Normally open and normally closed relay contacts.

Wiring Diagram

- Pin 1 "Normally Closed" Relay contact.
- Pin 2 "Normally Open" Relay contact.
- Pin 3 "Common" Relay contact
- Pin 4 "Reset In"
- Pin 5 "Trigger In" not used
- Pin 6 "Negative" 12VDC
- Pin 7 "Positive" 12VDC.

Ease of use

- Quick and easy timer adjustment.
- Apply / Remove relevant (L1 / L2) Links and Trigger link.
- Always remove power when changing link settings.

LINK	TIME	
No Link	15 minutes	
L2 On	30 minutes	
L1 On	60 minutes	
L1 + L2 On	90 Minutes	



KE-05-011-A