

PVC/ PVC CORE S- COLOUR CODED

Range : H01

Colour code to Def Spec 61-12



Special cable designs can be made

to customer specification

****Other colour coding available on request.

The H01 Range -PVC/PVC Cores with Tinned copper conductors

Without screen

Other variations of these cable available on request

Individual & Overall Mylar also available in Range H16 and

Overall (OAM)version available in Range H12

Tinned copper Braid (TCB) version available in Range H21

Helukabel Part No.	No. of Cores	Conductor size	Approx Nominal Ø- mm	Cable Construction
H012C22-GY	2	0.22mm ²	3.0	0.22mm ² (7/0.20mm (±0.2mm)) Tinned Copper conductors PVC insulation Cores laid up Grey PVC Sheath 440V Grade Colour coded Cores to Def Standard
H013C22-GY	3	0.22mm ²	3.4	
H014C22-GY	4	0.22mm ²	3.8	
H016C22-GY	6	0.22mm ²	4.4	
H018C22-GY	8	0.22mm ²	5.0	
H0110C22-GY	10	0.22mm ²	5.7	
H0112C22-GY	12	0.22mm ²	5.9	
H0118C22-GY	18	0.22mm ²	7.5	
H0120C22-GY	20	0.22mm ²	7.7	
H0125C22-GY	25	0.22mm ²	8.5	
H0130C22-GY	30	0.22mm ²	9.3	
H0136C22-GY	36	0.22mm ²	10.0	
H0150C22-GY	50	0.22mm ²	11.4	

H012P50-GY	2	0.50mm ²	5.4	0.50mm ² (16/0.20mm (±0.2mm)) Tinned Copper conductors PVC insulation Cores laid up Grey PVC Sheath 440V Grade Colour coded Cores to Def Standard
H013P50-GY	3	0.50mm ²	5.9	
H014P50-GY	4	0.50mm ²	6.3	
H016P50-GY	6	0.50mm ²	6.9	
H018P50-GY	8	0.50mm ²	8.0	
H0110P50-GY	10	0.50mm ²	9.1	
H0112P50-GY	12	0.50mm ²	9.4	
H0118P50-GY	18	0.50mm ²	11.4	
H0120P50-GY	20	0.50mm ²	12.5	
H0125P50-GY	25	0.50mm ²	13.3	
H0130P50-GY	30	0.50mm ²	15.0	
H0136P50-GY	36	0.50mm ²	16.0	
H0150P50-GY	50	0.50mm ²	18.5	

0.75mm² only manufactured on request

H011P100-GY	1	1.00mm ²	1.0mm ² (32 x 0.20mm (±0.2mm)) Plain Copper conductors PVC insulation Cores laid up Grey PVC Sheath 300/500V Grade Colour coded Cores to Def Standard
H012P100-GY	2	1.00mm ²	
H014P100-GY	4	1.00mm ²	
H018P100-GY	8	1.00mm ²	
H0112P100-GY	12	1.00mm ²	
H0116P100-GY	16	1.00mm ²	
H0120P100-GY	20	1.00mm ²	
H0124P100-GY	24	1.00mm ²	

H011P150-GY	1	1.50mm ²	1.50mm ² (30 x 0.25 (±0.2mm)) Plain Copper conductors PVC insulation Cores laid up Grey PVC Sheath 300/500V Grade Colour coded Cores to Def Standard
H012P150-GY	2	1.50mm ²	
H014P150-GY	4	1.50mm ²	
H018P150-GY	8	1.50mm ²	
H0112P150-GY	12	1.50mm ²	
H0116P150-GY	16	1.50mm ²	
H0120P150-GY	20	1.50mm ²	
H0124P150-GY	24	1.50mm ²	

Core / Pair colour coding available on request.

Other stranding may be supplemented

Large pair sizes are only available on special manufacture