

# PRODUCT SPECIFICATION MEC QUARTZ CRYSTAL

# FREQUENCY COMPONENTS

HC49S Series QUARTZ CRYSTAL SPECIFICATION

MOBICON HOLDINGS LTD.		
Prepared By	Sign.	Approved By
Leo Wong		C.H. Wong

www. mobicon. com



## SPECIFICATION OF CRYSTAL UNIT

### PART NO.:

### HC49S-10M1820F


### ELECTRICAL CHARACTERISTICS


- 1. Nominal Frequency
- 2. Holder Type
- 3. Frequency Tolerance
- 4. Equivalent Resistance
- 5. Insulation Resistance
- 6. Temperature Tolerance
- 7. Operating Temperature Range
- 8. Storage Temperature R ange
- 9. Loading Capacitance
- 10. Drive Level
- 11. Aging
- 12. Oscillation Mode

- 10 MHz
- HC49S
- <u>+</u> 20 ppm
- Ohm max.
- 500M Ohm @100V<sub>DC</sub>
- +/-50ppm at  $-10 \sim +60$ °C
- $-10 \sim +60^{\circ}$ C
- $-10 \sim +70^{\circ} \text{C}$
- 18 pF
- 100uW max.
- $\pm$  5ppm/ year max.
- **Fundamental**

Manufacturer's Code

### DIMENSIONs (mm)







4.88 + 0.2

Ø0.43 +0.05

-0.02

Prepared By: Leo Wong

Frequency Mark

Lot No.

DOC. No: HC49S-10M1820F



No.	Item	Condition of Test	
1	Drop Test	Dropping from 75cm height, 3 times on hard wooden board.	
2	Vibration Test	30 minutes in each direction 10 to 55 Hz, amplitude 0.7 ~ 0.9mm  Variation: Frequency drift < ± 20ppm	
3	Solderability	The dipping surface of the lead shall be at least 95% Covered with a Continuous new solder coating. Condition of test:  Temperature of solder bath: 230°C ± 5°C  Dipping time: 5 sec.	
4	Leakage	No bubbles coming up from interior of the holder. Insulation resistance: More than 500M Ohm Condition of test: Temperature of hot water: 90°C ~ 95°C Test time: 3 min.	

### REVIEW OF SPECIFICATIONS

- 1) When something get doubtful with this specifications, we shall jointly work to get an agreement.
- 2) This specification limits the quality of the components as a single unit. Please insure the component is thoroughly evaluated in your application circuit.
- 3) Please do not use this component in any application that deviates from its intended use as noted within the specification. It may cause any mishaps.
- 4) Please return one of this specification after your signature of acceptance. In case of no return within 3 months from submission date. This specification should be treated as accepted.



Prepared By: Leo Wong DOC. No: HC49S