

FEATURES

- **Slew Rate:** 7V/ μ s Typ
- **Gain-Bandwidth Product:** 14MHz Typ
- Fast Settling to 0.01%
2V Step to 200 μ V: 900ns Typ
10V Step to 1mV: 2.2 μ s Typ
- Excellent DC Precision in All Packages
Input Offset Voltage: 275 μ V Max
Input Offset Voltage Drift: 6 μ V/ $^{\circ}$ C Max
Input Offset Current: 30nA Max
Input Bias Current: 125nA Max
Open-Loop Gain: 1200V/mV Min
- Single Supply Operation
Input Voltage Range Includes Ground
Output Swings to Ground While Sinking Current
- Low Input Noise Voltage: 12nV/ \sqrt{Hz} Typ
- Low Input Noise Current: 0.2pA/ \sqrt{Hz} Typ
- Specified on 3.3V, 5V and \pm 15V
- Large Output Drive Current: 20mA Min
- Low Supply Current per Amplifier: 1.8mA Max
- Dual in 8-Pin DIP and SO-8
- Quad in 14-Pin DIP and Narrow SO-16

Note: For applications requiring higher slew rate, see the LT1213/LT1214 and LT1215/LT1216 data sheets.

 LTC and LT are registered trademarks of Linear Technology Corporation.

DESCRIPTION

The LT®1211 is a dual, single supply precision op amp with a 14MHz gain-bandwidth product and a 7V/ μ s slew rate. The LT1212 is a quad version of the same amplifier. The DC precision of the LT1211/LT1212 eliminates trims in most systems while providing high frequency performance not usually found in single supply amplifiers.


The LT1211/LT1212 will operate on any supply greater than 2.5V and less than 36V total. These amplifiers are specified on single 3.3V, single 5V and \pm 15V supplies, and only require 1.3mA of quiescent supply current per amplifier. The inputs can be driven beyond the supplies without damage or phase reversal of the output. The minimum output drive is 20mA, ideal for driving low impedance loads.

APPLICATIONS

- 2.5V Full-Scale 12-Bit Systems: $V_{OS} \leq 0.45$ LSB
- 10V Full-Scale 16-Bit Systems: $V_{OS} \leq 1.8$ LSB
- Active Filters
- Photo Diode Amplifiers
- DAC Current-to-Voltage Amplifiers
- Battery-Powered Systems


TYPICAL APPLICATION

Input Bias Current Cancellation



1211/12 TA01

Input Current vs Input Voltage



1211/12 TA02





LT1211/LT1212

ABSOLUTE MAXIMUM RATINGS

Total Supply Voltage (V^+ to V^-)	36V
Input Current	$\pm 15\text{mA}$
Output Short-Circuit Duration (Note 1)	Continuous
Operating Temperature Range	
LT1211C/LT1212C	-40°C to 85°C
LT1211I/LT1212I	-40°C to 85°C
LT1211M	-55°C to 125°C

Specified Temperature Range	
LT1211C/LT1212C/	
LT1211I/LT1212I (Note 5)	-40°C to 85°C
LT1211M	-55°C to 125°C
Storage Temperature Range	-65°C to 150°C
Junction Temperature (Note 2)	
Plastic Package (N8, S8, N, S)	150°C
Ceramic Package (J8)	175°C
Lead Temperature (Soldering, 10 sec)	300°C

PACKAGE/ORDER INFORMATION

TOP VIEW	ORDER PART NUMBER	TOP VIEW	ORDER PART NUMBER
	LT1211CN8 LT1211ACN8 LT1211IN8 LT1211MJ8 LT1211AMJ8		LT1211CS8 LT1211IS8
		S8 PACKAGE 8-LEAD PLASTIC SO	S8 PART MARKING 1211 1211I
T _{JMAX} = 175°C, θ _{JA} = 100°C/W (J) T _{JMAX} = 150°C, θ _{JA} = 100°C/W (N)		T _{JMAX} = 150°C, θ _{JA} = 150°C/W	
TOP VIEW	ORDER PART NUMBER	TOP VIEW	ORDER PART NUMBER
	LT1212CN LT1212IN		LT1212CS LT1212IS
N PACKAGE 14-LEAD PDIP		S PACKAGE 16-LEAD PLASTIC SO	
T _{JMAX} = 150°C, θ _{JA} = 70°C/W		T _{JMAX} = 150°C, θ _{JA} = 100°C/W	

AVAILABLE OPTIONS

NUMBER OF OP AMPS	T _A RANGE	MAX V _{OS} (25°C)	MAX TC V _{OS} ($\Delta V_{OS}/\Delta T$)	PACKAGE		
				CERAMIC (J)	PLASTIC DIP (N)	SURFACE MOUNT (S)
Two (Dual)	-40°C to 85°C	150μV	1.5μV/°C		LT1211ACN8	
		275μV	3μV/°C		LT1211CN8, LT1211IN8	
		275μV	6μV/°C			LT1211CS8, LT1211IS8

AVAILABLE OPTIONS

NUMBER OF OP AMPS	T _A RANGE	MAX V _{OS} (25°C)	MAX TC V _{OS} (ΔV _{OS} /ΔT)	PACKAGE		
				CERAMIC (J)	PLASTIC DIP (N)	SURFACE MOUNT (S)
Two (Dual)	−55°C to 125°C	150µV	1.5µV/°C	LT1211AMJ8		
		275µV	3µV/°C	LT1211MJ8		
Four (Quad)	−40°C to 85°C	275µV	6µV/°C		LT1212CN, LT1212IN	LT1212CS, LT1212IS

5V ELECTRICAL CHARACTERISTICS

V_S = 5V, V_{CM} = 0.5V, V_{OUT} = 0.5V, T_A = 25°C, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1211AC LT1211AM			LT1211C/LT1211M LT1212C			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
V _{OS}	Input Offset Voltage		75	150	100	275			µV
ΔV _{OS} ΔTime	Long-Term Input Offset Voltage Stability		0.5		0.6				µV/Mo
I _{OS}	Input Offset Current		5	20	5	30			nA
I _B	Input Bias Current		50	100	60	125			nA
	Input Noise Voltage	0.1Hz to 10Hz	250		250				nV _{P-P}
e _n	Input Noise Voltage Density	f ₀ = 10Hz f ₀ = 1000Hz	12.5 12.0		12.5 12.0				nV/√Hz nV/√Hz
i _n	Input Noise Current Density	f ₀ = 10Hz f ₀ = 1000Hz	0.9 0.2		0.9 0.2				pA/√Hz pA/√Hz
	Input Resistance (Note 3)	Differential Mode Common Mode	10 500	40	10 500	40			MΩ MΩ
	Input Capacitance	f = 1MHz	10		10				pF
	Input Voltage Range		3.5 0	3.8 −0.3	3.5 0	3.8 −0.3			V V
CMRR	Common-Mode Rejection Ratio	V _{CM} = 0V to 3.5V	90	105	86	102			dB
PSRR	Power Supply Rejection Ratio	V _S = 2.5V to 12.5V	90	115	87	110			dB
A _{VOL}	Large-Signal Voltage Gain	V _O = 0.05V to 3.7V, R _L = 500Ω	250	560	250	560			V/mV
	Maximum Output Voltage Swing (Note 4)	Output High, No Load Output High, I _{SOURCE} = 1mA Output High, I _{SOURCE} = 15mA	4.30 4.20 3.85	4.40 4.30 4.00	4.30 4.20 3.85	4.40 4.30 4.00			V
		Output Low, No Load Output Low, I _{SINK} = 1mA Output Low, I _{SINK} = 15mA	0.003 0.047 0.362	0.006 0.065 0.500	0.003 0.047 0.362	0.006 0.065 0.500			V
I _O	Maximum Output Current	(Note 9)	±20	±50	±20	±50			mA
SR	Slew Rate	A _V = −2		4		4			V/µs
GBW	Gain-Bandwidth Product	f = 100kHz		13		13			MHz
I _S	Supply Current per Amplifier		0.9	1.3	1.8	0.9	1.3	1.8	mA
	Minimum Supply Voltage	Single Supply		2.2	2.5		2.2	2.5	V
	Full Power Bandwidth	A _V = 1, V _O = 2.5V _{P-P}		300		300			kHz
t _r , t _f	Rise Time, Fall Time	A _V = 1, 10% to 90%, V _O = 100mV		45		45			ns
OS	Overshoot	A _V = 1, V _O = 100mV		25		25			%
t _{PD}	Propagation Delay	A _V = 1, V _O = 100mV		36		36			ns
t _S	Settling Time	0.01%, A _V = 1, ΔV _O = 2V		900		900			ns
	Open-Loop Output Resistance	I _O = 0mA, f = 5MHz		75		75			Ω
THD	Total Harmonic Distortion	A _V = 1, V _O = 1V _{RMS} , 20Hz to 20kHz		0.001		0.001			%

5V ELECTRICAL CHARACTERISTICS

$V_S = 5V$, $V_{CM} = 0.5V$, $V_{OUT} = 0.5V$, $-55^\circ C \leq T_A \leq 125^\circ C$, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1211AM			LT1211M			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{OS}	Input Offset Voltage		140	250		200	500		μV
$\frac{\Delta V_{OS}}{\Delta T}$	Input Offset Voltage Drift (Note 3)		0.7	1.5		1	3		$\mu V/^\circ C$
I_{OS}	Input Offset Current		15	40		25	75		nA
I_B	Input Bias Current		75	130		85	160		nA
	Input Voltage Range		3.1 0.4	3.2 0.2		3.1 0.4	3.2 0.2		V V
CMRR	Common-Mode Rejection Ratio	$V_{CM} = 0.4V$ to $3.1V$	87	104		81	101		dB
PSRR	Power Supply Rejection Ratio	$V_S = 2.5V$ to $12.5V$	87	113		84	109		dB
A_{VOL}	Large-Signal Voltage Gain	$V_O = 0.05V$ to $3.7V$, $R_L = 500\Omega$	100	250		100	250		V/mV
	Maximum Output Voltage Swing (Note 4)	Output High, No Load Output High, $I_{SOURCE} = 1mA$ Output High, $I_{SOURCE} = 10mA$	4.10 3.95 3.70	4.20 4.10 3.90		4.10 3.95 3.70	4.20 4.10 3.90		V V V
		Output Low, No Load Output Low, $I_{SINK} = 1mA$ Output Low, $I_{SINK} = 10mA$	0.007 0.060 0.350	0.010 0.085 0.500		0.007 0.060 0.350	0.010 0.085 0.500		mV mV mV
I_S	Supply Current per Amplifier		0.5	1.7	2.5	0.5	1.7	2.5	mA

$\pm 15V$ ELECTRICAL CHARACTERISTICS

$V_S = \pm 15V$, $V_{CM} = 0V$, $V_{OUT} = 0V$, $T_A = 25^\circ C$, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1211AC			LT1211C/LT1211M			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{OS}	Input Offset Voltage		125	400		150	550		μV
I_{OS}	Input Offset Current		5	20		5	30		nA
I_B	Input Bias Current		45	95		50	120		nA
	Input Voltage Range		13.5 -15.0	13.8 -15.3		13.5 -15.0	13.8 -15.3		V V
CMRR	Common-Mode Rejection Ratio	$V_{CM} = -15V$ to $13.5V$	90	105		86	102		dB
PSRR	Power Supply Rejection Ratio	$V_S = \pm 2V$ to $\pm 18V$	90	113		87	110		dB
A_{VOL}	Large-Signal Voltage Gain	$V_O = 0V$ to $\pm 10V$, $R_L = 2k$	1200	5000		1200	5000		V/mV
	Maximum Output Voltage Swing	Output High, $I_{SOURCE} = 15mA$ Output Low, $I_{SINK} = 15mA$	13.8 -14.4	14.0 -14.6		13.8 -14.4	14.0 -14.6		V V
I_O	Maximum Output Current (Note 9)		± 20	± 50		± 20	± 50		mA
SR	Slew Rate	$A_V = -2$ (Note 6)	5	7		5	7		$V/\mu s$
GBW	Gain-Bandwidth Product	$f = 100kHz$	8	14		8	14		MHz
I_S	Supply Current per Amplifier		0.9	1.8	2.5	0.9	1.8	2.5	mA
	Channel Separation	$V_O = \pm 10V$, $R_L = 2k$	128	140		128	140		dB
	Minimum Supply Voltage	Equal Split Supplies	± 1.2	± 2.0		± 1.2	± 2.0		V
	Full Power Bandwidth	$A_V = 1$, $V_O = 20V_{P-P}$	60			60			kHz
	Settling Time	$0.01\%, A_V = 1, \Delta V_O = 10V$	2.2			2.2			μs

LT1211/LT1212

ELECTRICAL CHARACTERISTICS

Note 1: A heat sink may be required to keep the junction temperature below absolute maximum when the output is shorted indefinitely.

Note 2: T_J is calculated from the ambient temperature T_A and power dissipation P_D according to the following formulas:

$$\text{LT1211MJ8, LT1211AMJ8: } T_J = T_A + (P_D \times 100^\circ\text{C/W})$$

$$\text{LT1211CN8, LT1211ACN8: } T_J = T_A + (P_D \times 100^\circ\text{C/W})$$

LT1211CS8:

$$T_J = T_A + (P_D \times 150^\circ\text{C/W})$$

LT1212CN:

$$T_J = T_A + (P_D \times 70^\circ\text{C/W})$$

LT1212CS:

$$T_J = T_A + (P_D \times 100^\circ\text{C/W})$$

Note 3: This parameter is not 100% tested.

Note 4: Guaranteed by correlation to 3.3V and ± 15 V tests.

Note 5: The LT1211C/LT1212C are guaranteed to meet specified performance from 0°C to 70°C and are designed, characterized and expected to meet these extended temperature limits, but are not tested at -40°C and 85°C . The LT1211I/LT1212I are guaranteed to meet the extended temperature limits.

Note 6: Slew rate is measured between ± 8.5 V on an output swing of ± 10 V on ± 15 V supplies.


Note 7: Most LT1211/LT1212 electrical characteristics change very little with supply voltage. See the 5V tables for characteristics not listed in the 3.3V table.

Note 8: Guaranteed by correlation to 5V and ± 15 V tests.


Note 9: Guaranteed by correlation to 3.3V tests.

TYPICAL PERFORMANCE CHARACTERISTICS


Distribution of Input Offset Voltage




Distribution of Offset Voltage Drift with Temperature




Distribution of Input Offset Voltage




Distribution of Input Offset Voltage












Distribution of Offset Voltage Drift with Temperature



Distribution of Input Offset Voltage












TYPICAL PERFORMANCE CHARACTERISTICS




LT1211/LT1212

TYPICAL PERFORMANCE CHARACTERISTICS




TYPICAL PERFORMANCE CHARACTERISTICS

5V Small-Signal Response




1211/12 G25

5V Large-Signal Response




1211/12 G26


5V Large-Signal Response




1211/12 G27

 $\pm 15V$ Small-Signal Response

1211/12 G28


 $\pm 15V$ Large-Signal Response

1211/12 G29

 $\pm 15V$ Large-Signal Response


1211/12 G30

5V Settling




1211/12 G31

±15V Settling



1211/12 G32

Settling Time to 0.01% vs Output Step




1211/12 G33

LT1211/LT1212


TYPICAL PERFORMANCE CHARACTERISTICS

Supply Current vs Supply Voltage




1211/12 G34

Supply Current vs Temperature




1211/12 G35

Warm-Up Drift vs Time




1211/12 G36

Input Bias Current vs Temperature




1211/12 G37

Input Bias Current vs Common-Mode Voltage




1211/12 G38

Common-Mode Range vs Temperature




1211/12 G39

Input Noise Current, Noise Voltage Density vs Frequency




1211/12 G40

Common-Mode Rejection Ratio vs Frequency



1211/12 G41

Input Referred Power Supply Rejection Ratio vs Frequency



1211/12 G42

APPLICATIONS INFORMATION

Supply Voltage

The LT1211/LT1212 op amps are fully functional and all internal bias circuits are in regulation with 2.2V of supply. The amplifiers will continue to function with as little as 1.5V, although the input common-mode range and the phase margin are about gone. The minimum operating supply voltage is guaranteed by the PSRR tests which are done with the input common mode equal to 500mV and a minimum supply voltage of 2.5V. The LT1211/LT1212 are guaranteed over the full –55°C to 125°C range with a minimum supply voltage of 2.5V.

The positive supply pin of the LT1211/LT1212 should be bypassed with a small capacitor (about 0.01µF) within an inch of the pin. When driving heavy loads and for good settling time, an additional 4.7µF capacitor should be used. When using split supplies, the same is true for the negative supply pin.

Power Dissipation

The LT1211/LT1212 amplifiers combine high speed and large output current drive into very small packages. Because these amplifiers work over a very wide supply range, it is possible to exceed the maximum junction temperature under certain conditions. To insure that the LT1211/LT1212 are used properly, calculate the worst case power dissipation, define the maximum ambient temperature, select the appropriate package and then calculate the maximum junction temperature.

The worst case amplifier power dissipation is the total of the quiescent current times the total power supply voltage plus the power in the IC due to the load. The quiescent supply current of the LT1211/LT1212 has a positive temperature coefficient. The maximum supply current of each amplifier at 125°C is given by the following formula:

$$I_{SMAX} = 2.5 + 0.036 \cdot (V_S - 5) \text{ in mA}$$

V_S is the total supply voltage.

The power in the IC due to the load is a function of the output voltage, the supply voltage and load resistance. The worst case occurs when the output voltage is at half supply, if it can go that far, or its maximum value if it cannot reach half supply.

For example, calculate the worst case power dissipation while operating on ±15V supplies and driving a 500Ω load.

$$I_{SMAX} = 2.5 + 0.036 \cdot (30 - 5) = 3.4\text{mA}$$

$$P_{DMAX} = 2 \cdot V_S \cdot I_{SMAX} + (V_S - V_{OMAX}) \cdot V_{OMAX}/R_L$$

$$\begin{aligned} P_{DMAX} &= 2 \cdot 15\text{V} \times 3.4\text{mA} + (15\text{V} - 7.5\text{V}) \cdot 7.5\text{V}/500 \\ &= 0.102 + 0.113 = 0.215\text{W per Amp} \end{aligned}$$

If this is the quad LT1212, the total power in the package is four times that, or 0.860W. Now calculate how much the die temperature will rise above the ambient. The total power dissipation times the thermal resistance of the package gives the amount of temperature rise. For this example, in the SO surface mount package, the thermal resistance is 100°C/W junction-to-ambient in still air.

$$\begin{aligned} \text{Temperature Rise} &= P_{DMAX} \cdot \theta_{JA} = 0.860\text{W} \cdot 100\text{°C/W} \\ &= 86\text{°C} \end{aligned}$$

The maximum junction temperature allowed in the plastic package is 150°C. Therefore the maximum ambient allowed is the maximum junction temperature less the temperature rise.

$$\text{Maximum Ambient} = 150\text{°C} - 86\text{°C} = 64\text{°C}$$

That means the SO quad can only be operated at or below 64°C on ±15V supplies with a 500Ω load.

As a guideline to help in the selection of the LT1211/LT1212, the following table describes the maximum supply voltage that can be used with each part based on the following assumptions:

1. The maximum ambient is 70°C or 125°C depending on the part rating.
2. The load is 500Ω, includes the feedback resistors.
3. The output can be anywhere between the supplies.

PART	MAX SUPPLIES	MAX POWER AT MAX T _A
LT1211MJ8	19.5V or ±16.4V	500mW
LT1211CN8	25.2V or ±18.0V	800mW
LT1211CS8	20.3V or ±17.1V	533mW
LT1212CN	21.0V or ±17.8V	1143mW
LT1212CS	17.3V or ±14.4V	800mW

APPLICATIONS INFORMATION

Inputs

Typically, at room temperature, the inputs of the LT1211/LT1212 can common mode 400mV below ground (V^-) and to within 1.2V of the positive supply with the amplifier still functional. However the input bias current and offset voltage will shift as shown in the characteristic curves. For full precision performance, the common-mode range should be limited between ground (V^-) and 1.5V below the positive supply.

When either of the inputs is taken below ground (V^-) by more than about 700mV, that input bias current will increase dramatically. The current is limited by internal 100 Ω resistors between the input pins and diodes to each supply. The output will remain low (no phase reversal) for inputs 1.3V below ground (V^-). If the output does not have to sink current, such as in a single supply system with a 1k load to ground, there is no phase reversal for inputs up to 8V below ground.

There are no clamps across the inputs of the LT1211/LT1212 and therefore each input can be forced to any voltage between the supplies. The input current will remain constant at about 60nA over most of this range. When an input gets closer than 1.5V to the positive supply, that input current will gradually decrease to zero until the input goes above the supply, then it will increase due to the previously mentioned diodes. If the inverting input is held more positive than the noninverting input by 200mV or more, while at the same time the noninverting input is within 300mV of ground (V^-), then the supply current will increase by 1mA and the noninverting input current will increase to about 10 μ A. This should be kept in mind in comparator applications where the inverting input stays above ground (V^-) and the noninverting input is at or near ground (V^-).

Output

The output of the LT1211/LT1212 will swing to within 0.60V of the positive supply with no load. The open-loop output resistance, when the output is driven hard into the

positive rail, is about 100 Ω as the output starts to source current; this resistance drops to about 25 Ω as the current increases. Therefore when the output sources 1mA, the output will swing to within 0.7V of the positive supply. While sourcing 20mA, it is within 1.1V of the positive supply.

The output of the LT1211/LT1212 will swing to within 3mV of the negative supply while sinking zero current. Thus, in a typical single supply application with the load going to ground, the output will go to within 3mV of ground. The open-loop output resistance when the output is driven hard into the negative rail is about 44 Ω at low currents and reduces to about 24 Ω at high currents. Therefore, when the output sinks 1mA, the output is about 42mV above the negative supply and while sinking 20mA, it is about 480mV above it.

The output of the LT1211/LT1212 has reverse-biased diodes to each supply. If the output is forced beyond either supply, unlimited currents will flow. If the current is transient and limited to several hundred mA, no damage will occur.

Feedback Components

Because the input currents of the LT1211/LT1212 are less than 125nA, it is possible to use high value feedback resistors to set the gain. However, care must be taken to insure that the pole that is formed by the feedback resistors and the input capacitance does not degrade the stability of the amplifier. For example, if a single supply, noninverting gain of two is set with two 20k resistors, the LT1211/LT1212 will probably oscillate. This is because the amplifier goes open-loop at 3MHz (6dB of gain) and has 50° of phase margin. The feedback resistors and the 10pF input capacitance generate a pole at 1.6MHz that introduces 63° of phase shift at 3MHz! The solution is simple; use lower value resistors or add a feedback capacitor of 10pF or more.



APPLICATIONS INFORMATION

Comparator Applications


Sometimes it is desirable to use an op amp as a comparator. When operating the LT1211/LT1212 on a single 3.3V or 5V supply, the output interfaces directly with most TTL and CMOS logic.

The response time of the LT1211/LT1212 is a strong function of the amount of input overdrive as shown in the

following photos. These amplifiers are unity-gain stable op amps and not fast comparators, therefore, the logic being driven may oscillate due to the long transition time. The output can be speeded up by adding 20mV or more of hysteresis (positive feedback), but the offset is then a function of the input direction.




SIMPLIFIED SCHEMATIC




LT1211/LT1212

TYPICAL APPLICATIONS

1A Voltage-Controlled Current Source




1A Voltage-Controlled Current Sink



PACKAGE DESCRIPTION

Dimensions in inches (millimeters) unless otherwise noted.

J8 Package
8-Lead CERDIP (Narrow 0.300, Hermetic)
(LTC DWG # 05-08-1110)




J8.1197

PACKAGE DESCRIPTION


Dimensions in inches (millimeters) unless otherwise noted.

N8 Package
8-Lead PDIP (Narrow 0.300)
(LTC DWG # 05-08-1510)



*THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.010 INCH (0.254mm)

N Package
14-Lead PDIP (Narrow 0.300)
(LTC DWG # 05-08-1510)




*THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.010 INCH (0.254mm)

PACKAGE DESCRIPTION

Dimensions in inches (millimeters) unless otherwise noted.

S8 Package
8-Lead Plastic Small Outline (Narrow 0.150)
(LTC DWG # 05-08-1610)




*DIMENSION DOES NOT INCLUDE MOLD FLASH. MOLD FLASH
SHALL NOT EXCEED 0.006" (0.152mm) PER SIDE

**DIMENSION DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD
FLASH SHALL NOT EXCEED 0.010" (0.254mm) PER SIDE

S08 0996

S Package
16-Lead Plastic Small Outline (Narrow 0.150)
(LTC DWG # 05-08-1610)



*DIMENSION DOES NOT INCLUDE MOLD FLASH. MOLD FLASH
SHALL NOT EXCEED 0.006" (0.152mm) PER SIDE


**DIMENSION DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD
FLASH SHALL NOT EXCEED 0.010" (0.254mm) PER SIDE

S16 0695

LT1211/LT1212

TYPICAL APPLICATION

Single Supply, 100kHz, 4th Order Butterworth Lowpass Filter




12-BIT ACCURATE SIGNAL RANGE FROM 6mV TO 1.8V ON 3.3V SINGLE SUPPLY.
MAXIMUM OUTPUT OFFSET ERROR IS 676 μ V.

FOR EACH 2ND ORDER SECTION:

$$W_0^2 = \frac{1}{C_1 C_2 R_1 R_2}$$

$$R_1 = \frac{1}{W_0 Q C_1}$$

$$R_2 = \frac{Q}{W_0 C_2}$$



1211/12 TA03b

RELATED PARTS

PART NUMBER	DESCRIPTION	COMMENTS
LT1213/LT1214	28MHz, 12V/ μ s, Single Supply Dual and Quad Precision Op Amps	Twice as Fast as LT1211
LT1215/LT1216	23MHz, 50V/ μ s, Single Supply Dual and Quad Precision Op Amps	Seven Times LT1211 Slew Rate
LT1498/LT1499	10MHz, 6V/ μ s, Dual/Quad Rail-to-Rail Input and Output Precision C-Load Op Amps	Rail-to-Rail LT1211
LT1630/LT1631	30MHz, 10V/ μ s, Dual/Quad Rail-to-Rail Input and Output Precision Op Amps	Rail-to-Rail LT1213
LT1632/LT1633	45MHz, 45V/ μ s, Dual/Quad Rail-to-Rail Input and Output Precision Op Amps	Rail-to-Rail LT1215