




K2420x (FROM K2420 TO K24237)
CURRENT

A	B	C	D	E
1A	3A	5A	6A	10A


SPECIFICATIONS

Rated Voltage		125V AC / 250V AC
Leakage Current		0.8mA max. 250 V, 50Hz
Test Voltage	Line To line	1450 V DC
	Line To Ground	2250 V DC
Insulation Resistance		100MΩ min. 250 V DC
Operating Temperature		-25°C ~ 85°C


K2420 A /B /D /E
EMI FILTER (TERMINAL 6.3mm)




K24214F
EMI FILTER 15A (TERMINAL 6.3mm)




K24202 A /B /D /E
EMI FILTER (PCB TERMINAL)




K24230 A /B /D /E
EMI FILTER (PCB TERMINAL)




K24204 A /B /D /E
EMI FILTER W/O FUSE (TERMINAL 6.3mm)




K24232 A /B /D /E
EMI FILTER (TERMINAL 3.0mm)




K24205 A /D
EMI FILTER W/O FUSE (TERMINAL 6.3mm)




K24235 A /B /D /E
EMI FILTER (TERMINAL 6.3mm)




K2421 A /B /D /E
EMI FILTER (TERMINAL 6.3mm)



K24236 A /B /D /E
EMI FILTER (TERMINAL 6.3mm)



K24212 A /B /D /E
EMI FILTER (SOLDER LUG TERMINAL)



K24237 A /B /D /E
EMI FILTER (SCREW OUTPUT TERMINAL)

