

AC MINI MAGNETIC CONTACTORS - 1 NO OR 1 NC AUXILIARY - 3 POLE



Part Number	Current Rating		400V		Auxiliary Contact	Dimensions H x W x D
	AC3	AC1	kW	HP		
UKC1-6M-1A	6A	12A	2,2	3	1 NO	55 x 44 x 44mm
UKC1-6M-1B	6A	12A	2,2	3	1 NC	55 x 44 x 44mm
UKC1-9M-1A	9A	16A	4	5,5	1 NO	55 x 45 x 50mm
UKC1-9M-1B	9A	16A	4	5,5	1 NC	55 x 45 x 50mm
UKC1-12M-1A	12A	20A	5,5	7,5	1 NO	55 x 45 x 50mm
UKC1-12M-1B	12A	20A	5,5	7,5	1 NC	55 x 45 x 50mm
UKC1-16M-1A	16A	20A	7,5	10	1 NO	55 x 45 x 50mm
UKC1-16M-1B	16A	20A	7,5	10	1 NC	55 x 45 x 50mm

Available Coil Voltages AC ONLY. *Please Specify:

A=12V, B=24V, E=48V, F=110V, M=230V, Q=415V or T=525V. (AC ONLY)

AC MAGNETIC CONTACTORS - 1 NO OR 1 NC AUXILIARY - 3 POLE



Part Number	Current Rating		400V		Auxiliary Contact	Dimensions H x W x D
	AC3	AC1	kW	HP		
MCE-D0910	9A	20A	4	5,5	1 NO	74 x 45 x 80mm
MCE-D0901	9A	20A	4	5,5	1 NC	74 x 45 x 80mm
MCE-D1210	12A	25A	5,5	7,5	1 NO	74 x 45 x 80mm
MCE-D1201	12A	25A	5,5	7,5	1 NC	74 x 45 x 80mm
MCE-D1810	18A	32A	7,5	10	1 NO	74 x 45 x 80mm
MCE-D1801	18A	32A	7,5	10	1 NC	74 x 45 x 80mm

Available Coil Voltages AC ONLY. *Please Specify:

A=12V, B=24V, E=48V, F=110V, M=230V, Q=415V or T=525V. (AC ONLY)

AC MAGNETIC CONTACTORS - 1 NO OR 1 NC AUXILIARY - 3 POLE



Part Number	Current Rating		400V		Auxiliary Contact	Dimensions H x W x D
	AC3	AC1	kW	HP		
MCE-D2510	25A	40A	11	15	1 NO	85 x 56 x 93mm
MCE-D2501	25A	40A	11	15	1 NC	85 x 56 x 93mm
MCE-D3210	32A	50A	15	20	1 NO	85 x 56 x 93mm
MCE-D3201	32A	50A	15	20	1 NC	85 x 56 x 93mm
MCE-D3810	38A	50A	15	20	1 NO	85 x 56 x 93mm
MCE-D3801	38A	50A	15	20	1 NC	85 x 56 x 93mm

Available Coil Voltages AC ONLY. *Please Specify:

A=12V, B=24V, E=48V, F=110V, M=230V, Q=415V or T=525V. (AC ONLY)

AC MAGNETIC CONTACTORS - 1 NO AND 1 NC AUXILIARY - 3 POLE



Part Number	Current Rating		400V		Auxiliary Contact	Dimensions H x W x D
	AC3	AC1	kW	HP		
MCE-D4011	40A	60A	18,5	25	1+1	125 x 75 x 114mm
MCE-D5011	50A	80A	22	30	1+1	125 x 75 x 114mm
MCE-D6511	65A	80A	30	40	1+1	125 x 75 x 114mm
MCE-D8011	80A	125A	37	50	1+1	125 x 75 x 123mm
MCE-D9511	95A	125A	45	60	1+1	125 x 75 x 123mm

Available Coil Voltages AC ONLY. *Please Specify:

A=12V, B=24V, E=48V, F=110V, M=230V, Q=415V or T=525V. (AC ONLY)