



MD012 Connector, Plug



MD012-350



MD012-500M



DIMENSIONS/POSITIONS

		MD012-350	MD012-500M
間距	Pitch	3.50mm	5.00mm
位數	Poles	2 ~ 24Poles	2 ~ 3Poles
尺寸a	Dimension a	3.50mm	5.00mm
長度 A	Length	A= 3.50xP(P≥2)	A= 5.00xP(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Brass, Tin Plated	Brass, Tin Plated
夾片	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
螺紋	Screw Thread	M2.0, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	16 ~ 24AWG	14 ~ 22AWG
最大緊固扭矩	Tightening Torque, Max.	3.0 Lb-in	3.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _N	Nominal Current I _N	8A	10A
額定橫截面	Nominal Cross Section	1.5mm ²	1.5mm ²
最大負載電流	Maximum load current	8A	10A
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓, UL/CUL Nominal voltage, UL/CUL		125V	300V
額定電流, UL/CUL Nominal current, UL/CUL		8A	15A

