

HP & NX Plastic P-Clips

Features and Benefits

Manufactured from Nylon these P-Clips offer good temperature resistance as well as offering high strength. A feature of the NX clips is their versatility to accept cables of differing sizes through the use of a range of fixing holes - this feature enables users to minimise stock holding of a large range of clips.

Application

For permanent, or semi-permanent, cable fixings this range of P-Clips can be used in many industries, their light weight makes them particularly suitable for use in areas such as aircraft and aerospace where minimising weight, but retaining a strong fixing, is vitally important.

Material Data

RoHS	Material	Polyamide 6.6 (PA66)
	Colour	Natural (NT), Black (BK)
	Operating Temperature	-40°C to +85°C Continuous, (+105°C for 500 h)
	Flammability	UL94 V2
	HF (halogenfree)	

Technical Table

Code	Type	Width (W)	Wall (WT)	Fixing Hole Ø (FH)	Bundle Ø max.	Fixing Hole Centres (F)	Radius (R)	Material	Colour
*NX0	H1P	10.0	0.8	4.2	3.2	8.5	0.5	PA66HS	Black (BK)
*NX1	H2P	10.0	1.0	4.2	5.0	9.5	1.0	PA66HS	Black (BK)
*NX2	H3P	10.0	1.0	4.2	6.5	10.0	1.0	PA66HS	Black (BK)
*NX3	H4P	10.0	1.2	4.2	8.0	10.0	1.0	PA66HS	Black (BK)
*NX3	H4P	10.0	1.2	4.2	8.0	10.0	1.0	PA66	Natural (NT)
*NX4	H5P	10.0	1.2	4.2	9.5	11.0	1.0	PA66HS	Black (BK)
*NX5	H6P	10.0	1.2	4.2	11.0	13.0	1.0	PA66HS	Black (BK)
*NX6	H7P	10.0	1.2	4.2	12.5	14.0	1.5	PA66HS	Black (BK)
*NX8	NX8	—	13	—	—	—	—	PA66	Black (BK)
*NX11	NX11	12.6	1.3	4.0	20.0	—	—	PA66	Black (BK)
*NX14	NX14	16.0	15	4.3	25.4	—	—	PA66	Black (BK)
	H1P	10.0	0.8	4.2	3.2	8.5	0.5	PA66	Natural (NT), Black (BK)
	H2P	10.0	1.0	4.2	5.0	9.5	1.0	PA66	—
	H3P	10.0	1.0	4.2	6.5	10.0	1.0	PA66	Natural (NT)
	H5P	10.0	1.2	4.2	9.5	11.0	1.0	PA66	Natural (NT)
	H6P	10.0	1.2	4.2	11.0	13.0	1.0	PA66	Natural (NT)
	H7P	10.0	1.2	4.2	12.5	14.0	1.5	PA66	Natural (NT)
	H8P	10.0	1.5	4.2	14.0	15.0	1.5	PA66HS	Black (BK)
	H8P	10.0	1.5	4.2	14.0	15.0	1.5	PA66	Natural (NT)
	H9P	10.0	15	4.2	16.0	16.0	1.5	PA66	Natural (NT)
	H10P	10.0	1.5	4.2	17.5	17.0	1.5	PA66	Natural (NT)
	H11P	10.0	1.5	4.2	19.0	18.0	2.0	PA66	Natural (NT)
	H12P	10.0	1.5	4.2	20.5	19.0	2.0	PA66	Natural (NT)
	H13P	12.0	1.5	5.2	22.0	20.5	2.0	PA66	Natural (NT)
	H14P	12.0	1.5	5.2	24.0	21.5	2.0	PA66	Natural (NT)
	H15P	12.0	1.5	5.2	25.5	23.0	2.5	PA66	Natural (NT)
	H16P	12.0	1.5	5.2	28.5	24.0	2.5	PA66	Natural (NT)
	H17P	12.0	1.5	5.2	31.5	26.0	2.5	PA66	Natural (NT)
	H18P	12.0	1.5	5.2	35.0	27.5	2.5	PA66	Natural (NT)

All dimensions in mm. Subject to technical changes.

* Local Product


Standard Colour - Black (BK) / Natural (NT) on request




P-Clip NX.

Material Data

RoHS	Material	Polyamide 6.6 Heat Stabilised (PA66HS)
	Colour	Black (BK)
	Operating Temperature	-40°C to +105°C Continuous, (+145°C for 500 h)
	Flammability	UL94 V2
	HF (halogenfree)	



P-Clip H1P-H18P



P-Clip NX8-14