



和瑞電子(中山)有限公司

Henry Electronic (Zhong Shan) Co. Ltd.

URL: <http://www.3lcoil.com>

SPECIFICATION FOR APPROVAL 樣品承認書



CUSTOMER(客戶): H55 萬寶剛 Mobicon		PAGE: 1 OF 1																																		
3L P/N: PK1820-471K-UL		YOUR REF.:																																		
1.MECHANICAL DIMENSIONS (外形尺寸): DRAW NO.:PK-UL 		<table border="1"> <thead> <tr> <th>Item 項目</th> <th>Spec.(mm) (規格)</th> <th>Typ. (參考值)</th> </tr> </thead> <tbody> <tr><td>A</td><td>24.0 MAX</td><td>21.29</td></tr> <tr><td>B</td><td>15.0 MIN</td><td></td></tr> <tr><td>C</td><td>12.5+-1.0</td><td>12.51</td></tr> <tr><td>D</td><td>21.0 MAX</td><td>18.72</td></tr> <tr><td>E</td><td>1.0 +- 0.05</td><td>0.99</td></tr> <tr><td>F</td><td>3.0 MAX</td><td></td></tr> <tr><td>G</td><td></td><td></td></tr> <tr><td>H</td><td></td><td></td></tr> <tr><td>I</td><td></td><td></td></tr> <tr><td>J</td><td></td><td></td></tr> </tbody> </table>	Item 項目	Spec.(mm) (規格)	Typ. (參考值)	A	24.0 MAX	21.29	B	15.0 MIN		C	12.5+-1.0	12.51	D	21.0 MAX	18.72	E	1.0 +- 0.05	0.99	F	3.0 MAX		G			H			I			J			Marking (印字):
Item 項目	Spec.(mm) (規格)	Typ. (參考值)																																		
A	24.0 MAX	21.29																																		
B	15.0 MIN																																			
C	12.5+-1.0	12.51																																		
D	21.0 MAX	18.72																																		
E	1.0 +- 0.05	0.99																																		
F	3.0 MAX																																			
G																																				
H																																				
I																																				
J																																				
2.ELECTRICAL CHARACTERISTICS (電特性要求):																																				
Item (項目)	Specifications (規格)	Typ.(參考值)	Test equipments (測試設備):																																	
L	470uH +- 10%	471.6uH	CHENHWA 100 LCR METER																																	
Test Freq.	@1kHz 0.25V		CHENHWA 100 LCR METER																																	
DCR	200mOHM MAX	158.1mOH	CHENHWA 502 OHM METER																																	
R.Current	2.8A		HP4284A WITH HP42841A CURRENT SOURCE																																	
Turns	83.5Ts REF																																			
Ope.Temp.	-20 TO 85°C		HC-D3M TEMP. & HUMIDITY CHAMBER																																	
CUSTOMER APPROVED (客戶確認)		APPROVED(確認)	CHECKED(檢查)																																	
ISSUED DATE(出版日期): 2008/11/27 PRINT DATE(出圖日期): 2008/11/27 REV(版次):XA																																				