

ROHS

SPECIFICATIONS

Current Rating: 3 AMP
 Insulator Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.
 Withstanding Voltage: AC 500V
 Operating Temperature: -40℃ to +105℃
 Max Processing Temp: 180° -230° for 30-60 seconds
 Insulator: Glass filled PBT (UL94V-0), Black
 Contacts: Brass

Ordering Information

A NJ 254- XX S X XX X 01
 127=1.27mm 6-64P S=180度 A=PBT L=长耳扣 10=Gold flash P=袋装
 200=2.0mm R=90度 B=PA66 S=短耳扣 11=镀金1U H=盒装
 254=2.54mm M=SMT C=PA6T D=PA9T E=LCP 12=镀金1.5U T=管装
 13=镀金2U R=卷装
 14=镀金3U
 15=镀金5U
 16=镀金10U
 17=镀金15U
 18=镀金30U
 20=镀锡
 21=半金锡1U

深圳市深琪博电子有限公司

>10	±0.30	SCALE: 比例:	1:1	APPD. 核准:		TITLE: 型号:	2.54牛角 NP 180度 PC3.5
3~10	±0.20	UNIT: 单位:	mm	CHKD. 审核:		Part No: 料号:	ANJ254-XXSXXX01
0~3	±0.10	ANGLE	±1°	DR. 设计:	金承鑫 2021.04.16	Part No: 客户料号:	

注: F在18P及18P以上才有

PCB LAYOUT