Part Numbering

CERAFIL[®] for AM

(Part Number)

SF	Ρ	KA	455K	D4A	-B0
0	2	8	4	6	6

Product ID

Product ID	
SF	Ceramic Filters
CF	Ceramic Filters

2Oscillation/Numbers of Element

Code	Oscillation/Numbers of Element	
U	1 Element Area Expansion mode	
Z	2 Elements Area Expansion mode	
Р	4 Elements Area Expansion mode	

3Structure/Size

Code	Structure/Size
L	Lead Type
C□/K□	Chip Type

 \Box is "**A**" or subsequent code, which indicates the structure/size. It varies depending on vibration mode and number of elements.

One of the second se

Expressed by four-digit alphanumerics. The unit is in hertz (Hz). Capital letter " \mathbf{K} " following three figures expresses the unit of "kHz".

5Product Specification

Code	Product Specification
D4A	3 digits alphanumeric indicates product specification of 3dB or 6dB frequency tolerance.

□□A indicates standard type.

6 Packaging

Code	Packaging
-В0	Bulk
-R0	Embossed Taping (ø180mm)
-R1	Embossed Taping (ø330mm)
-M0	Magazine Cassette

Radial taping is applied to lead type and embossed taping to chip type. With non-standard products, three-digit alphanumerics indicating "Individual Specification" is added between "@Product Specification" and "@Packaging".

