

2 ×16 LCD Controller Module

1. Introductions


The LCD Keypad shield is developed for Arduino compatible boards, to provide a user-friendly interface that allows users to go through the menu, make selections etc. It consists of a 1602 white character blue backlight LCD. The keypad consists of 5 keys — select, up, right, down and left. To save the digital IO pins, the keypad interface uses only one ADC channel. The key value is read through a 5 stage voltage divider.

Specifications:

- Blue Backlight with white words
- uses 4 Bit Arduino LCD Library
- Left, Right, Up, Down and Select buttons
- Screen contrast adjustment
- Arduino Reset button

2 Pin Instruction

Pin	Function
Analog 0	Button (select, up, right, down and left)
Digital 4	DB4(the LCD)
Digital 5	DB5(the LCD)
Digital 6	DB6(the LCD)
Digital 7	DB7(the LCD)
Digital 8	RS
Digital 9	RW
Digital 10	Backlit Control



3. Example

Here is a example to test the button function of this module.

*****code begin*****

```
//Sample using LiquidCrystal library
#include <LiquidCrystal.h>
```

```
*****
```

This program will test the LCD panel and the buttons

Mark Bramwell, July 2010

```
******/
```

```
// select the pins used on the LCD panel
LiquidCrystal lcd(8, 9, 4, 5, 6, 7);
```

```
// define some values used by the panel and buttons
int lcd_key      = 0;
int adc_key_in   = 0;
#define btnRIGHT   0
#define btnUP       1
#define btnDOWN    2
#define btnLEFT    3
```

```

#define btnSELECT 4
#define btnNONE    5

// read the buttons
int read_LCD_buttons()
{
    adc_key_in = analogRead(0);          // read the value from the sensor
    // my buttons when read are centered at these values: 0, 144, 329, 504, 741
    // we add approx 50 to those values and check to see if we are close
    if (adc_key_in > 1000) return btnNONE; // We make this the 1st option for speed reasons since it
    will be the most likely result
    // For V1.1 us this threshold
    if (adc_key_in < 50)   return btnRIGHT;
    if (adc_key_in < 250)  return btnUP;
    if (adc_key_in < 450)  return btnDOWN;
    if (adc_key_in < 650)  return btnLEFT;
    if (adc_key_in < 850)  return btnSELECT;

    // For V1.0 comment the other threshold and use the one below:
/*
    if (adc_key_in < 50)   return btnRIGHT;
    if (adc_key_in < 195)  return btnUP;
    if (adc_key_in < 380)  return btnDOWN;
    if (adc_key_in < 555)  return btnLEFT;
    if (adc_key_in < 790)  return btnSELECT;
*/
}

return btnNONE; // when all others fail, return this...
}

void setup()
{
    lcd.begin(16, 2);           // start the library
    lcd.setCursor(0,0);
    lcd.print("Push the buttons"); // print a simple message
}

void loop()
{
    lcd.setCursor(9,1);         // move cursor to second line "1" and 9 spaces over
    lcd.print(millis()/1000);   // display seconds elapsed since power-up
}

```

```

lcd.setCursor(0,1);           // move to the begining of the second line
lcd_key = read_LCD_buttons(); // read the buttons

switch (lcd_key)           // depending on which button was pushed, we perform an
action
{
    case btnRIGHT:
    {
        lcd.print("RIGHT ");
        break;
    }
    case btnLEFT:
    {
        lcd.print("LEFT   ");
        break;
    }
    case btnUP:
    {
        lcd.print("UP     ");
        break;
    }
    case btnDOWN:
    {
        lcd.print("DOWN   ");
        break;
    }
    case btnSELECT:
    {
        lcd.print("SELECT");
        break;
    }
    case btnNONE:
    {
        lcd.print("NONE   ");
        break;
    }
}
}

*****Code End*****

```