



本厂宣传资料由国赛科技印制，仅用于展示本企业系列的新产品资料，本手册只汇编了国赛科技部分代表性产品，国赛科技固部分产品正在变更，升级版或采用更新的生产工艺改进本手册有关内容，或对本手册的印刷错误及相关资料信息进行必要的修改或更新时，恕不另行通知，若遇成您重商不便，敬请谅解。

新目录发行，旧目录自动废除！

This manual is printed by guosai technology, only used to show the relative information of this series. guosai technology keep the right of amending this manual due to technical improved or new production processused, or mistake amended etc without notice Please contact with our company to confirm the relative information when place the order.

New catalog distribution, old directory automatic abolition



扫一扫 公众号

深圳市国赛科技发展有限公司

SHENZHEN GUOSAI TECHNOLOGY DEVELOPMENT CO., LTD.

公司地址：深圳市福田区振中路新亚洲电子商城4A026

Company Add: A4026 New Asian Electronic Mall,

Zhenzhong road, Futian, Shenzhen, China.

Tel: 0755-61306777 Fax: 0755-61306203

展销地址：深圳市华强北路1015号华强电子世界三号楼B054

Huaqiang North Road, Futian, Shenzhen, China.

Tel: 0755-83759072 Fax: 0755-83759072

http://www.szguosai.com QQ: 3432352545

E-mail: szgskj@hotmail.com



乐清市国赛科技发展有限公司

YUEQING GUOSAI TECHNOLOGY DEVELOPMENT CO., LTD.

新厂地址：浙江省乐清经济开发区纬十五路202号

Factory Add: No. 202 Wei fifteen Road,

Economic Development Zone, Yueqing, Zhejiang

工厂地址：浙江省乐清市北白象镇马路角工业区

Factory Add: Malujiao Industrial Zone,

Beibaixiang, Yueqing, Zhejiang

P.C.: 325604

Tel: 0577-61891155 Fax: 0577-61891159

http://www.guosai.cc QQ: 2628462568

中文域名：www.国赛.com

E-mail: guosai@guosai.cc



国赛接线端子 GS TERMINAL 2018



TERMINAL 接线端子



品质为基 全球服务
Quality Based Serve The World



PVC绝缘护套叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Spade Terminal
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color
						W	L	F	E	DΦ	
SV 0.5-3	0.2~0.75 (24~18)	0.5	10A	#4	3.2	5.7	19.5	5.1	10.0	2.7	黄 yellow
SV 0.5-4				#8	4.3	6.4	19.5	5.3		1.3	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color
						W	L	F	E	DΦ	
SV 1.25-3	0.5-1.5 (22-16)	0.75	19A	#4	3.2	5.7	21.8	6.5			红 red
SV 1.25-3.5S				#6	3.7	5.7	21.8	6.5			
SV 1.25-3.5L				#6	3.7	6.4	21.8	6.5			
SV 1.25-4S				#8	4.3	6.4	21.8	6.5			
SV 1.25-4M				#8	4.3	7.2	21.8	6.5	10.7	4.2	
SV 1.25-4L				#8	4.3	8.1	21.8	6.5			
SV 1.25-5S				#10	5.3	8.1	21.8	6.5			
SV 1.25-5L				#10	5.3	9.3	21.8	6.5			
SV 1.25-6S				1/4	6.4	9.5	21.8	6.5			
SV 1.25-6L				1/4	6.4	12.0	28.0	11.0			

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color
						W	L	F	E	DΦ	
SV2-3	1.5-2.5 (16-14)	0.8	27A	#4	3.2	5.7	21.7	6.5			蓝 blue
SV2-3.5S				#6	3.7	5.7	21.7	6.5			
SV2-3.5L				#6	3.7	6.2	21.7	6.5			
SV2-4S				#8	4.3	6.4	21.7	6.5			
SV2-4M				#8	4.3	7.2	21.7	6.5	10.7	4.9	
SV2-4L				#8	4.3	8.1	21.7	6.5			
SV2-5S				#10	5.3	8.1	21.7	6.5			
SV2-5L				#10	5.3	9.5	21.7	6.5			
SV2-6S				1/4	6.4	9.5	21.7	6.5			
SV2-6L				1/4	6.4	12.0	27.7	11.0			



PVC绝缘护套叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Spade Terminal
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




SPADE TERMINAL

型号 Item NO	导线载面积mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	DΦ		dΦ
SV 3.5-3	2.5-4 (14-12)	1.0	37A	#4	3.2	5.7	25.8	7.0			黑 black	
SV 3.5-4S				#8	4.3	7.2	25.8	7.0				
SV 3.5-4				#8	4.3	8.0	25.8	7.0	13.8	5.8		3.0
SV 3.5-5				#10	5.3	8.0	25.8	7.0				
SV 3.5-6				1/4	6.4	12.0	28.8	8.7				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color
						W	L	F	E	DΦ	
SV 5.5-3.5	4-6 (12-10)	1.0	48A	#6	3.7	7.2	24.8	7.5			黄 yellow
SV 5.5-4S				#8	4.3	8.3	26.0	7.5			
SV 5.5-4L				#8	4.3	9.0	26.0	7.5			
SV 5.5-5				#10	5.3	9.0	26.0	7.5	13.6	6.4	
SV 5.5-6S				1/4	6.4	9.0	26.0	7.5			
SV 5.5-6L				1/4	6.4	12.0	32.0	12.0			
SV 5.5-8				5/16	8.4	14.0	30.8	11.5			

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		
SV 8-4	6-10 (8)	1.2	62A	#8	4.3	8.7	30.8	9.1			红 red	
SV 8-5				#10	5.3	11.0	31.8	8.3	17.0	8.0		4.5
SV 8-6				1/4	6.3	12.0	32.8	8.7				



尼龙绝缘护套叉形端子(适用于软线)


- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Spade Terminal**
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 1.25-3				#4	3.2	5.7	22.0	6.5		
SVN 1.25-3.5S				#6	3.7	5.7	22.0	6.5		
SVN 1.25-3.5L				#6	3.7	6.4	22.0	6.5		
SVN 1.25-4S				#8	4.3	6.4	22.0	6.5		
SVN 1.25-4M				#8	4.3	7.2	22.0	6.5		
SVN 1.25-4L	0.5-1.5 (22-16)	0.75	19A	#8	4.3	8.1	22.0	6.5	11.0	4.3
SVN 1.25-5S				#10	5.3	8.1	22.0	6.5		1.7
SVN 1.25-5L				#10	5.3	9.3	22.0	6.5		
SVN 1.25-6S				1/4	6.4	9.5	22.0	6.5		
SVN 1.25-6L				1/4	6.4	12.0	28.0	11.0		

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 2-3				#4	3.2	5.7	22.0	6.5		
SVN 2-3.5S				#6	3.7	5.7	22.0	6.5		
SVN 2-3.5L				#6	3.7	6.2	22.0	6.5		
SVN 2-4S				#8	4.3	6.4	22.0	6.5		
SVN 2-4M				#8	4.3	7.2	22.0	6.5		
SVN 2-4L	1.5-2.5 (16-14)	0.8	27A	#8	4.3	8.1	22.0	6.5	11.0	4.9
SVN 2-5S				#10	5.3	8.1	22.0	6.5		
SVN 2-5L				#10	5.3	9.3	22.0	6.5		
SVN 2-6S				1/4	6.4	9.5	22.0	6.5		
SVN 2-6L				1/4	6.4	12.0	28.0	11.0		



尼龙绝缘护套叉形端子(适用于软线)



- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Spade Terminal**
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 3.5-3				#4	3.2	5.7	25.2	7.0		
SVN 3.5-4S				#8	4.3	7.2	25.2	7.0		
SVN 3.5-4	2.5-4 (14-12)	1.0	37A	#8	4.3	8.0	25.2	7.0	13.3	6.0
SVN 3.5-5				#10	5.3	8.0	25.2	7.0		
SVN 3.5-6				1/4	6.4	12.0	28.7	8.7		

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 5.5-3.5				#6	3.7	7.2	24.8	7.5		
SVN 5.5-4S				#8	4.3	8.3	26.5	7.5		
SVN 5.5-4L				#8	4.3	9.0	26.5	7.5		
SVN 5.5-5	4-6 (12-10)	1.0	48A	#10	5.3	9.0	26.5	7.5	14.0	6.6
SVN 5.5-6S				1/4	6.4	9.0	26.5	7.5		
SVN 5.5-6L				1/4	6.4	12.0	32.0	12.0		
SVN 5.5-8				5/16	8.4	14.0	30.7	11.5		




- 尼龙绝缘护套叉形端子(加铜套)(适用于软线)
- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Spade Terminal(Double Copper Sleeve)
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 1.25-3 D				#4	3.2	5.7	22.0	6.5		
SVN 1.25-3.5SD				#6	3.7	5.7	22.0	6.5		
SVN 1.25-3.5LD				#6	3.7	6.4	22.0	6.5		
SVN 1.25-4SD				#8	4.3	6.4	22.0	6.5		
SVN 1.25-4MD				#8	4.3	7.2	22.0	6.5		
SVN 1.25-4LD		0.75	19A	#8	4.3	8.1	22.0	6.5		
SVN 1.25-5SD				#10	5.3	8.1	22.0	6.5		
SVN 1.25-5LD				#10	5.3	9.3	22.0	6.5		
SVN 1.25-6SD				1/4	6.4	9.5	22.0	6.5		
SVN 1.25-6LD				1/4	6.4	12.0	28.0	11.0		
									11.0	3.8
										1.7
										红 red

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 2-3 D				#4	3.2	5.7	22.0	6.5		
SVN 2-3.5SD				#6	3.7	5.7	22.0	6.5		
SVN 2-3.5LD				#6	3.7	6.2	22.0	6.5		
SVN 2-4SD				#8	4.3	6.4	22.0	6.5		
SVN 2-4MD				#8	4.3	7.2	22.0	6.5		
SVN 2-4LD		0.8	27A	#8	4.3	8.1	22.0	6.5		
SVN 2-5SD				#10	5.3	8.1	22.0	6.5		
SVN 2-5LD				#10	5.3	9.3	22.0	6.5		
SVN 2-6SD				1/4	6.4	9.5	22.0	6.5		
SVN 2-6LD				1/4	6.4	12.0	28.0	11.0		
									11.0	4.4
										2.3
										蓝 blue




- 尼龙绝缘护套叉形端子(加铜套)(适用于软线)
- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Spade Terminal(Double Copper Sleeve)
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 3.5-3 D				#4	3.2	5.7	25.2	7.0		
SVN 3.5-4SD				#8	4.3	7.2	25.2	7.0		
SVN 3.5-4 D		1.0	37A	#8	4.3	8.0	25.2	7.0	13.3	5.4
SVN 3.5-5 D				#10	5.3	8.0	25.2	7.0		
SVN 3.5-6 D				1/4	6.4	12.0	28.2	8.7		
										黑 black

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E	dφ
SVN 5.5-3.5 D				#6	3.7	7.2	24.8	7.5		
SVN 5.5-4SD				#8	4.3	8.3	26.5	7.5		
SVN 5.5-4LD				#8	4.3	9.0	26.5	7.5		
SVN 5.5-5 D	4-6 (12-10)	1.0	48A	#10	5.3	9.0	26.5	7.5	14.0	6.1
SVN 5.5-6SD				1/4	6.4	9.0	26.5	7.5		
SVN 5.5-6LD				1/4	6.4	12.0	32.2	12.0		
SVN 5.5-8 D				5/16	8.4	14.0	30.7	11.5		
										黄 yellow



无绝缘护套折弯叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Non-Insulated Flange Spade Terminal

- Terminal Body: Copper
- Plating: Tin




SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)			
						W	L	F	E DΦ
FSNB 1.25-3.5	0.5-1.5 (22-16)	0.75	19A	#6	3.7	6.2	16.5	5.1	
FSNB 1.25-4				#8	4.3	7.2	16.5	5.1	4.8 3.4
FSNB 1.25-5				#10	5.3	8.0	16.5	5.1	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)			
						W	L	F	E DΦ
FSNB 2-3.5	1.5-2.5 (16-14)	0.8	27A	#6	3.7	6.2	16.5	5.2	
FSNB 2-4				#8	4.3	7.2	16.5	5.2	4.8 4.1
FSNB 2-5				#10	5.3	8.0	16.5	5.2	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)			
						W	L	F	E DΦ
FSNB 5.5-3.5	4-6 (12-10)	1.0	48A	#6	3.7	8.1	18.5	7.5	
FSNB 5.5-4				#8	4.3	8.2	18.5	7.5	6 5.6
FSNB 5.5-5				#10	5.3	9.0	18.5	7.5	



PVC绝缘护套折弯叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Flange Spade Terminal

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E DΦ	
FSV 1.25-3.5	0.5-1.5 (22-16)	0.75	19A	#6	3.7	6.2	22.0	5.1		
FSV 1.25-4				#8	4.3	7.2	22.0	5.1	10.7 4.3	红 red
FSV 1.25-5				#10	5.3	8.0	22.0	5.1		

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E DΦ	
FSV 2-3.5	1.5-2.5 (16-24)	0.8	27A	#6	3.7	6.2	22.0	5.2		
FSV 2-4				#8	4.3	7.2	22.0	5.2	10.7 4.9	蓝 blue
FSV 2-5				#10	5.3	8.0	22.0	5.2		

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color
						W	L	F	E DΦ	
FSV 5.5-3.5	4-6 (12-10)	1.0	48A	#6	6.2	8.1	25.5	7.5		
FSV 5.5-4				#8	7.2	8.2	25.5	7.5	14.0 6.6	黄 yellow
FSV 5.5-5				#10	8.0	9.0	25.5	7.5		



尼龙绝缘护套折角叉形端子(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

Nylon-Insulated Flange Spade Terminal

- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin





SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color
						W	L	F	E	D φ	
FSVN 1.25-3.5	0.5-1.5 (22-16)	0.75	19A	#6	3.7	6.2	22.0	5.1			红 red
FSVN 1.25-4				#8	4.3	7.2	22.0	5.1	11.0	4.3	
FSVN 1.25-5				#10	5.3	8.0	22.0	5.1			

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	颜色 Color
FSVN 2-3.5	1.5-2.5 (16-14)	0.8	27A	#6	3.7	蓝 blue
FSVN 2-4				#8	4.3	
FSVN 2-5				#10	5.3	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	D φ		
FSVN 5.5-3.5	4-6 (12-10)	1.0	48A	#6	3.7	8.1	25.5	7.5			黄 yellow	
FSVN 5.5-4				#8	4.3	8.2	25.5	7.5	14.0	6.6		3.4
FSVN 5.5-5				#10	5.3	9.0	25.5	7.5				



尼龙绝缘护套折角叉形端子(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

Nylon-Insulated Flange Spade Terminal (Double Copper Sleeve)

- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	DΦ		
FSVN 1.25-3.5 D	0.5-1.5 (22-16)	0.75	19A	#6	3.7	6.2	22.0	5.1			红 red	
FSVN 1.25-4 D				#8	4.3	7.2	22.0	5.1	11.0	3.8		1.7
FSVN 1.25-5 D				#10	5.3	8.0	22.0	5.1				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	颜色 Color
FSVN 2-3.5 D	1.5-2.5 (16-14)	0.8	27A	#6	3.7	蓝 blue
FSVN 2-4 D				#8	4.3	
FSVN 2-5 D				#10	5.3	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		
FSVN 5.5-3.5 D	4-6 (12-10)	1.0	48A	#6	3.7	8.1	25.5	7.5			黄 yellow	
FSVN 5.5-4 D				#8	4.3	8.2	25.5	7.5	14.0	6.1		3.4
FSVN 5.5-5 D				#10	5.3	9.0	25.5	7.5				