

Modular Flat Type Telephone Cable UL AWM Style 20251 扁平型电话线



◆ APPLICATION 用途

For use with standard telephone, RJ11 & RJ45 modular crimp plugs. 用於标准电话RJ11 和RJ45 压接插头连线。

◆ DESCRIPTION 描述

Conductor : Tinned or bare, stranded copper.

Insulation : Polypropylene or PVC.

Cores : Two to Ten conductors.

Drain Wire : Tinned or bare copper

Shielding : AL. Foil

Sheath : PVC.

导体 : 镀锡或裸铜绞线

绝缘 : 聚丙烯或者聚氯乙烯

芯数 : 二到十芯

水线 : 镀锡或裸铜

屏蔽 : 铝箔

护套 : 聚氯乙烯

◆ TECHNICAL DATA 技术资料

Temperature rating : 60 °C

Rated Voltage : 150V

Applicable Standard : UL AWM 20251, UL758, UL1581

Comply with RoHS EU Directive.

额定温度 : 60°C

额定电压 : 150V

参考标准 : UL AWM 2919, UL758, UL 1581.

符合欧盟 RoHS 指令

Item No. 产品编号	Conductor 导体		Insulation 绝缘			Shielding 屏蔽	Sheath 护套
	AWG 规格	No. /mm 根数/外径	Cores 芯数	Nom. Thickness 标称厚度 (mm)	Nom. O.D 标称外径 (mm)	Material 材质	Nom. O.D 标称外径 (mm)
2012-18-001	28	7/0.12	4	0.25	0.95	***	2.5 x 5.0
2012-18-002	28	7/0.12	6	0.25	0.95	***	2.5 x 7.0
2012-18-003	28	7/0.12	8	0.25	0.95	***	2.5 x 8.8
2012-18-004	28	7/0.12	10	0.25	0.95	***	2.5 x 10.7
2012-18-005	26	7/0.15	4	0.25	0.95	***	2.5 x 5.0
2012-18-006	26	7/0.15	6	0.25	0.95	***	2.5 x 7.0
2012-18-007	26	7/0.15	8	0.25	0.95	***	2.5 x 9.0
2012-18-008	26	7/0.15	10	0.25	0.95	***	2.5 x 10.7
2012-18-009	26	7/0.16	4	0.20	0.95	AL. Foil	2.5 x 5.2
2012-18-010	26	7/0.16	6	0.20	0.95	AL. Foil	2.5 x 7.0
2012-18-011	26	7/0.16	8	0.20	0.95	AL. Foil	2.6 x 9.3