

MICRO SWITCHES

General purpose Z-type



Code Z15G-1701



Code Z15G-1702



Code Z15G-1703



Code Z15G-1704



Code Z15G-1744



Code Z15G-1300



Code Z15G-1305



Code Z15G-1306



Code Z15G-1307



Code Z15G-1705



Code Z15G-1308




Code Z15G-1318

Specifications

Contact resistance: 15mΩmax (initial)
Insulation resistance: 100MΩmin (at 500VDC)
Dielectric strength: 1 000VAC 50/60Hz for 1 min
Service life: Mechanically: 1 000 000 operations p/min
Electrically: 100 000 operations p/min
Current rating: 15A @ 250VAC C/O

Mounting holes



Terminal Cover for Z-type Micro Switches




Code AA8000


Type VS Micro switch (High mechanical life)




Code VS15P01C



Code VS15P02C




Code VS15P03C



Code VS15P04C




Code VS15P05C



Code VS15P06C



Code VS15P07C



Code P-CS-71

Specifications

Contact resistance: 15mΩmax (initial)
Insulation resistance: 100MΩmin (at 500VDC)
Dielectric strength: 1 000VAC 50/60Hz for 1 min
Service life: Mechanically: 1 000 000 operations p/min
Electrically: 100 000 operations p/min
Current rating: VS: 1C/O 15A @ 250V
P-CS: 1C/O 5A @ 250V

Mounting holes

