


LED 2mm Yellow High-head with Yellow light Long Feet: 29mm 1.8-2.2V 20mA 2000-3000mcd 1k/bag
P/N: 181426

PACKAGE DIMENSIONS(UNIT: mm)

(DEVICE NO) XR-3R4UW
 2mm yellow high- head



ABSOLUTEMAXIMUM RATINGS: (Ta=25°C)

Characteristic	Forward Current	Forward Max. Current	Reverse Voltage	Power Dissipation	Operation Temperature	Storage Temperature	Soldering Temperature
Symbol	I _{FM} (mA)	I _{FM-MAX} (mA)	V _{RM} (V)	P _D (mW)	T _{OPR} (°C)	T _{STG} (°C)	T _{SLD} (°C)
Rate	20	100	5	120	-40~+70	-40~+85	260(3s~5s)

ELECTRO-OPTICAL CHARACTERISTICS: (Ta=25°C)

Type No.	Luminous Intensity Iv (mcd) If=20mA	Wavelength λ _D (nm) If=20mA	Forward Voltage V _F (V) If=20mA	Reverse Current If(μ A) V _R =5V	度 Power Angle 2 θ /2	Test Conditions If=20mA V _R =5V
3R4UW	2000-3000	588-595	1.8~2.2	10	120	