## 深圳市鸿泰机电科技有限公司 APPROVAL SHEET

型号 Model NO.: AC12025 220V 120\*120\*25mm Sleeve Bearing Wire: 24AWG



1. Scope of application:							
This product specification specifies the product performance and test methods as the							
basis for technical confirmation							
2. General characteristic							
2.1 Product application scop	oe						
This product is mainly used for ventilation and heat dissipation of automatic equipment such as ground automatic control device, electronic equipment, medical equipment, computer, power supply equipment, electric welding machine, packaging and printing equipment, satellite communication, numerical control machinery and so on.							
2.2 Standard test conditions	s:						
Generally, the test shall be conducted under the conditions of standard atmospheric pressure, temperature of 5 $^{\sim}$ 35 $^{\circ}$ C and relative humidity of less than 85%; The relative humidity in the specification is less than 25 $^{\circ}$ C, and the relative humidity in this standard is less than 60%							
2.3 Basis standard							
GB12350-2009 Safety requirements for small power motors							
CNCA-01C-013: 2007 implementation rules for compulsory certification of electrical and electronic products (small power motor)							
3. Product structure							

The product is composed of cylindrical aluminum alloy outer frame, PBT plastic fan blade and motor. It is installed through double-sided flange, with the characteristics of small volume, maintenance free and convenient installation. It also has the excellent performance of low noise, low vibration and reliable operation.

## 4. General characteristics

		Standard		
No.	Item	value	Unit	Remark
1	Product model	12025HBL		
2	<b>Outline Dimension</b>	120*120*25	mm	
3	Rated Voltage	AC220	V	
4	Starting Voltage	AC 187	V	
5	Frequency	50	Hz	
6	Rated current	0.07	Α	
7	Power	14	W	
8	Speed	1800	RPM	
	Airflow AT ZERO STATIC			
9	PRESSURE	1.6	m³/min	
10	Wind speed		m/s	
11	Temperature rise	50	°C	
12	Noise value	35	dBA	
13	CONNECTOR	1007#24AWG	mm	
14	Use environment	<b>−20</b> ~+60	°C	
15	Unit weight	0.26	KG	
16	Packing	60	PCS	

17 Lifetime 3000h

## Specifications of main materials

No.	Part name	Material	Safety regulation level	Safety code	Material manufacturer
1	Outer frame	ADC12			
2	Fan blade	PBT			
3	Stator and rotor	1300			
4	Copper wire	QA-1			
		Sleeve			
5	Bearing	Bearing			



